

XLS 12" Passive Radiator



Type Number: 830548

Features:

This new series of state-of-the-art subwoofers continue to enhance Peerless' reputation for delivering the highest quality components for bass in the world. Called the XLS - for "Extra Long Stroke" - these new audio transducers add even more excursion, and completely eliminate distortion.

See architecture notes for XLS Platform

Driver Highlights: Thick Nomex cone, 425 g moving mass

See application notes for XLS 12" subwoofer

Go to Architecture Notes



Specs:

Power handling		
Rated Noise Power (IEC 18.1)		W
100h RMS noise test (IEC)		W
Long-term Max Power (IEC 18.3)		W
Max linear SPL (rms) @ power		dB/W
Short Term Max power (IEC 18.2)		W
Voice Coil and Magnet Parameters		
Voice coil diameter		mm
Voice coil height		mm
Voice coil layers		
Height of the gap		mm
Linear excursion +/-		mm
Max mech. excursion +/-	24	mm
Flux density of gap		mWb
Total useful flux		mWb
Diameter of magnet		mm
Height of magnet		mm
Weight of magnet		Kg
Misc. Parameters		
Effective Frequency range (IEC 21.2)		Hz
Performance Temp. range (IEC 25.1.1)		°C
Damage Temp. range (IEC 25.1.2)		°C
Relative Humidity Range (IEC 25.2.1)		%
Damage Humidity Range (IEC 25.2.2)		%

Mechanical Dimensions:830548	
×	

Frequency: 830548