PROFESSIONAL SERIES

LA 15850

Shallow 15 inch high power cast frame woofer with a 4 inch voice coil and super strong cone body. The inverted dust cap allows close placement to phase plugs used in many horn loaded designs.

- 1600 W Program Power
- 15" Nominal Diameter
- 8 O

APPLICATION		ENCLOSURE	
Midrange		Sealed Box	
Midbass	V	Vented Box	~
Woofer	V	Scoop Loading	~
Subwoofer	V	Horn Loading	~
Bass Guitar			

SPECIFICATION

Nominal Basket Diameter	15", 381 mm
Nominal Impedance*	8Ω
Power Rating*	
Program Power	1600 W
Nominal Power	800 W
Resonance	34 Hz
Usable Frequency Range	45 Hz – 1.5 kHz
Sensitivity*	96.2 dB
Magnet Weight	109 oz.
Gap Height	0.375", 9.5 mm
Voice Coil Diameter	4", 102 mm

EMINENCE WAYN WENTERGO.COM PROFESSIONAL SERIES TOTAL TO

THIELE & SMALL PARAMETERS


MOUNTING INFORMATION

34 Hz	Recommended Enclosure Volume	
5.83 Ω	Sealed	N/A
1 mH		
9.27	Vented	46.72-127.43 liters,
0.34		1.65-4.5 cu.ft.
0.33	Driver Volume Displaced	0.145 cu.ft., 4.1 liters
8.27 cu.ft., 234.15 liters	Overall Diameter	15.3", 388.6 mm
351.1 cc	Baffle Hole Diameter	14.08", 357.6 mm
0.23 mm/N	Front Sealing Gasket	Yes
18.98 T-M	Rear Sealing Gasket	Yes
98 grams	Mounting Holes Diameter	0.26", 6.5 mm
100	Mounting Holes B.C.D.	14.57", 370.1 mm
4.1 mm	Depth	5.5", 139.7 mm
856.3 cm2	Net Weight	21.4 lbs , 9.71 kg
12.2 mm	Shipping Weight	23.6 lbs , 10.7 kg
	5.83 Ω 1 mH 9.27 0.34 0.33 8.27 cu.ft., 234.15 liters 351.1 cc 0.23 mm/N 18.98 T-M 98 grams 100 4.1 mm 856.3 cm2	Sealed 1 mH

MATERIALS OF CONSTRUCTION

Copper voice coil	
Polyimide former	
Ferrite magnet	
Core and Spider Land extended	
Die-cast aluminum basket	
Water resistant treated paper cone	
Paper cone edge	
Water resistant treated paper dust cap	

FREQUENCY RESPONSE & IMPEDANCE CURVE*



See footnotes on page 155 for information regarding usable frequency range, nominal impedance, power rating and sensitivity.