REDCOAT GUITAR SERIES

RF10C

A ceramic version of our popular Red Fang 12 alnico. A round and beefy British tone with abundant harmonic detail, full lows, and nice grit and chime.

10" 50 WATTS 8 Ω



SPECIFICATION MOUNTING INFORMATION MATERIALS OF CONSTRUCTION

Net Weight


Shipping Weight

Nominal Basket Diameter	10", 254 mm	Enclosure Type		Copper voice coil
Nominal Impedance*	8 Ω	Closed Back	Acceptable	Nomex former
Power Rating*	50 W	Open Back	Acceptable	Ferrite magnet
Resonance (Fs)	105 Hz	Driver Volume Displaced	0.039 cu.ft., 1.1 liters	Non-vented core
Usable Frequency Range	80 Hz – 4.2 kHz	Overall Diameter	10.11", 256.8 mm	Pressed steel basket
Sensitivity*	100.4 dB	Baffle Hole Diameter	9.13", 231.9 mm	Paper cone
DC Resistance (Re)	5.98 Ω	Depth	4", 101.6 mm	Paper cone edge
Qts	0.53	Front Sealing Gasket	Yes	Zurette dust cap
Magnet Weight	38 oz.	Rear Sealing Gasket	Yes	
Gap Height	0.31", 8 mm	Mounting Holes Diameter	0.23", 5.8 mm	
Voice Coil Diameter	1.75", 44 mm	Mounting Holes B.C.D.	9.6", 243.8 mm	

7.3 lbs , 3.31 kg

8.4 lbs , 3.81 kg

FREQUENCY RESPONSE & IMPEDANCE CURVE*







See footnotes on page 155 for information regarding usable frequency range, nominal impedance, power rating and sensitivity.