



SP-300PA

Order No.: 10.2980

Price upon request

PRODUCTINFOS

PA and power bass speakers, 175 W, 8 Ω (SP-300PA) and 4 Ω (SP-304PA)

• For bass and bass-midrange in medium-sized systems

TECHNICAL SPECIFICATIONS

SP-300PA

Impedance (Z)	8 Ω
Frequency range	f3-4,000 Hz
Resonant frequency (fs)	40 Hz
Power rating	175 W
Peak music power output	350 W
Sensitivity	93 dB/W/m
Suspension compl. (Cms)	0.35 mm/N
Moving mass (Mms)	45 g



SP-300PA

Mech. Q factor (Qms) 2.65 Electr. Q factor (Qes) 0.52 Total Q factor (Qts) 0.46 Equivalent volume (Vas) 150 l 6.9 Ω DC resistance (Re) Force factor (BxL) 10.5 Tm Voice coil induct. (Le) 0.5 mH Voice coil diameter Ø 39 mm Voice coil former aluminium Linear excursion (X_{MAX}) ±3.25 mm Eff. cone area (Sd) 514 cm²

Magnet weight 850 g

Magnet diameter Ø 125 mm

Mounting cutout Ø 280 cm

Mounting depth 130 mm

Dimensions Ø 305 mm x 130 mm

Outside diameter Ø 305 mm

Width Ø 305 mm

Depth 130 mm

Admiss. ambient temp. 0-40 °C

Weight 3 kg

Sales unit 1

Type of speaker 12"