

SPP-90 - Page: 1



SPP-90

Order No.: 10.1150

Price upon request

PRODUCTINFOS

Tweeter, 22 W, 8 Ω

- Low crossover frequency possible
- Closed basket

This series of speakers with polypropylene cone is very well-suited for replacing defective 8 Ω speakers in hifi speaker systems.

TECHNICAL SPECIFICATIONS

SPP-90	
Impedance (Z)	8 Ω
Frequency range	2,000-18,000 Hz
Resonant frequency (fs)	1,000 Hz
Power rating	22 W



SPP-90 - Page: 2

SPP-90

Peak music power output	45 W
Sensitivity	92 dB/W/m
DC resistance (Re)	6.5 Ω
Voice coil induct. (Le)	0.1 mH
Voice coil diameter	Ø 15 mm
Voice coil former	aluminium
Eff. cone area (Sd)	23 cm ²
Magnet weight	85 g
Magnet diameter	Ø 60 mm
Mounting cutout	Ø 61 mm
Mounting depth	25.7 mm
Dimensions	Ø 78 mm x 30 mm
Outside diameter	Ø 78 mm
Width	Ø 78 mm
Depth	30 mm
Admiss. ambient temp.	0-40 °C
Weight	0.23 kg
Sales unit	1
Type of speaker	3"