DP83864

DP83864 Quad GigPHYTER 10/100/1000 Ethernet Physical Layer



Literature Number: SNLS172B

ADVANCED INFORMATION

September 2003



DP83864 Quad GigPHYTER[™] 10/100/1000 Ethernet Physical Layer

General Description

The DP83864 is an extremely efficient full featured Quad Physical Layer transceiver with integrated PMD sublayers to support 10BASE-T, 100BASE-TX and 1000BASE-T Ethernet protocols.

The DP83864 contains four integrated ultra low power Gigabit Physical layers. It uses advanced 0.18 $\mu m,$ 1.8 V CMOS technology, fabricated at National's South Portland, Maine facilities.

The DP83864 is designed for easy implementation of 10/100/1000 Mb/s Ethernet LANs. Each port interfaces directly to Twisted Pair media via an external transformer. This device interfaces directly to the MAC layer through the IEEE 802.3u Standard Media Independent Interface (MII) or the IEEE 802.3z Gigabit Media Independent Interface (GMII). It also supports the reduced pin count RGMII (12 pins per port) and serial GMII (8 pins per port).

The DP83864 is a fourth generation of Gigabit Physical layer product with field proven architecture and performance. Its robust performance ensures drop in replacement of existing 10/100M equipment with 10/100/1000M Networking infrastructure.

Applications

The DP83864 fits applications in:

- Switches with 10/100/1000 Mb/s capable ports
- High speed uplink ports with redundancies (backbone)
- Servers with Quad Ethernet ports

© 2003 National Semiconductor Corporation

Features

- IEEE compliant 10BASE-T,100BASE-TX, 1000BASE-T
- Adaptive equalization and Baseline Wander comp.
- IEEE 802.3u Auto-Negotiation and Parallel Detection
- Fully auto-negotiates between 1000 Mb/s, 100 Mb/s, and 10 Mb/s full duplex and half duplex devices
- 2.5 V/3.3 V MAC interfaces:
 - IEEE 802.3u MII with programmable bus ordering
 - IEEE 802.3z GMII with programmable bus ordering
 - Reduced GMII (RGMII) ver. 1.3
 - Serial GMII (SGMII)
- LED support (Link10, Link100, Link1000, Activity and Duplex indicators); Direct drive LED's thru management
- User Programmable Interrupt
- A 25Mhz or 125Mhz oscillator as reference clock input
- PHY level CRC checking on received packets and PHY level CRC generation for test mode transmit packets
- 292 BGA package
- Power dissipation approximately 1 W / port
- 1.8 V CMOS (core & analog); 2.5 V (analog & I/O); 3.3 V is optional for 3.3 V I/O voltage
- One management port per chip
- Supports Auto-MDIX/polarity at all speeds
- One JTAG interface per chip





DP83864 Notes:



DP83864 Quad GigPHYTER™ 10/100/1000 Ethernet Physical Layer

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Audio	www.ti.com/audio	Communications and Telecom	www.ti.com/communications
Amplifiers	amplifier.ti.com	Computers and Peripherals	www.ti.com/computers
Data Converters	dataconverter.ti.com	Consumer Electronics	www.ti.com/consumer-apps
DLP® Products	www.dlp.com	Energy and Lighting	www.ti.com/energy
DSP	dsp.ti.com	Industrial	www.ti.com/industrial
Clocks and Timers	www.ti.com/clocks	Medical	www.ti.com/medical
Interface	interface.ti.com	Security	www.ti.com/security
Logic	logic.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Power Mgmt	power.ti.com	Transportation and Automotive	www.ti.com/automotive
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com		
OMAP Mobile Processors	www.ti.com/omap		
Wireless Connectivity	www.ti.com/wirelessconnectivity		

TI E2E Community Home Page

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2011, Texas Instruments Incorporated