

**MCM67A618B***Advance Information***64K x 18 Bit Asynchronous/  
Latched Address Fast Static RAM**

The MCM67A618B is a 1,179,648 bit latched address static random access memory organized as 65,536 words of 18 bits. The device integrates a 64K x 18 SRAM core with advanced peripheral circuitry consisting of address and data input latches, active low chip enable, separate upper and lower byte write strobes, and a fast output enable. This device has increased output drive capability supported by multiple power pins.

Address, data in, and chip enable latches are provided. When latch enables (AL for address and chip enables and DL for data in) are high, the address, data in, and chip enable latches are in the transparent state. If latch enables are tied high the device can be used as an asynchronous SRAM. When latch enables are low the address, data in, and chip enable latches are in the latched state. This input latch simplifies read and write cycles by guaranteeing address and data-in hold time in a simple fashion.


Dual write enables ( $\overline{LW}$  and  $\overline{UW}$ ) are provided to allow individually writeable bytes.  $\overline{LW}$  controls DQ0 – DQ8 (the lower bits) while  $\overline{UW}$  controls DQ9 – DQ17 (the upper bits).

Six pair of power and ground pins have been utilized and placed on the package for maximum performance.


The MCM67A618B will be available in a 52-pin plastic leaded chip carrier (PLCC).

This device is ideally suited for systems that require wide data bus widths, cache memory, and tag RAMs.

- Single 5 V  $\pm 5\%$  Power Supply
- Fast Access Times: 10 ns Max
- Byte Writeable via Dual Write Enables
- Separate Data Input Latch for Simplified Write Cycles
- Address and Chip Enable Input Latches
- Common Data Inputs and Data Outputs
- Output Enable Controlled Three-State Outputs
- 3.3 V I/O Compatible
- High Board Density 52-Lead PLCC Package



**FN PACKAGE  
PLASTIC  
CASE 778-02**

**PIN ASSIGNMENT****PIN NAMES**

A0 – A15	Address Inputs
AL	Address Latch
DL	Data Latch
$\overline{LW}$	Lower Byte Write Enable
$\overline{UW}$	Higher Byte Write Enable
$\overline{E}$	Chip Enable
$\overline{G}$	Output Enable
DQ0 – DQ17	Data Input/Output
VCC	+5 V Power Supply
VSS	Ground

All power supply and ground pins must be connected for proper operation of the device.

This document contains information on a new product. Specifications and information herein are subject to change without notice.

REV 4  
1/14/00





## DC OPERATING CONDITIONS AND CHARACTERISTICS

( $V_{CC} = 5.0\text{ V} \pm 5\%$ ,  $T_A = 0^\circ$  to  $70^\circ\text{C}$ , Unless Otherwise Noted)

### RECOMMENDED OPERATING CONDITIONS (Voltages referenced to $V_{SS} = 0\text{ V}$ )

Parameter	Symbol	Min	Max	Unit
Supply Voltage (Operating Voltage Range)	$V_{CC}$	4.75	5.25	V
Input High Voltage	$V_{IH}$	2.2	$V_{CC} + 0.3^{**}$	V
Input Low Voltage	$V_{IL}$	-0.5*	0.8	V

\*  $V_{IL}(\text{min}) = -0.5\text{ V dc}$ ;  $V_{IL}(\text{min}) = -2.0\text{ V ac}$  (pulse width  $\leq 20\text{ ns}$ ) for  $I \leq 20.0\text{ mA}$ .

\*\*  $V_{IH}(\text{max}) = V_{CC} + 0.3\text{ V dc}$ ;  $V_{IH}(\text{max}) = V_{CC} + 2.0\text{ V ac}$  (pulse width  $\leq 20\text{ ns}$ ) for  $I \leq 20.0\text{ mA}$ .

### DC CHARACTERISTICS

Parameter	Symbol	Min	Max	Unit
Input Leakage Current (All Inputs, $V_{in} = 0$ to $V_{CC}$ )	$I_{lkg(I)}$	—	$\pm 1.0$	$\mu\text{A}$
Output Leakage Current ( $\bar{G} = V_{IH}$ )	$I_{lkg(O)}$	—	$\pm 1.0$	$\mu\text{A}$
AC Supply Current (Device Selected, All Outputs Open, Freq = Max, $V_{CC} = \text{Max}$ )	$I_{CCA}$	—	290	mA
CMOS Standby Supply Current (Device Deselected, Freq = 0, $V_{DD} = \text{Max}$ , All Inputs Static at CMOS Levels $V_{in} \leq V_{SS} + 0.2\text{ V}$ or $\geq V_{CC} - 0.2\text{ V}$ )	$I_{SB2}$	—	20	mA
AC Standby Supply Current (Device Deselected, Freq = Max, $V_{DD} = \text{Max}$ , All Inputs Toggling at CMOS Levels $V_{in} \leq V_{SS} + 0.2\text{ V}$ or $\geq V_{CC} - 0.2\text{ V}$ )	$I_{SB4}$	—	95	mA
Output Low Voltage ( $I_{OL} = 8.0\text{ mA}$ )	$V_{OL}$	—	0.4	V
Output High Voltage ( $I_{OH} = -4.0\text{ mA}$ )	$V_{OH}$	2.4	3.3	V

### CAPACITANCE (f = 1.0 MHz, $T_A = 25^\circ\text{C}$ , Periodically Sampled Rather Than 100% Tested)

Characteristic	Symbol	Typ	Max	Unit
Input Capacitance	$C_{in}$	4	5	pF
Input/Output Capacitance	$C_{I/O}$	6	8	pF

## AC OPERATING CONDITIONS AND CHARACTERISTICS

( $V_{CC} = 5.0\text{ V} \pm 5\%$ ,  $T_A = 0^\circ$  to  $70^\circ\text{C}$ , Unless Otherwise Noted)

Input Timing Measurement Reference Level ..... 1.5 V  
 Input Pulse Levels ..... 0 to 3.0 V  
 Input Rise/Fall Time ..... 3 ns


Output Timing Reference Level ..... 1.5 V  
 Output Load ..... Figure 1 Unless Otherwise Noted

### ASYNCHRONOUS READ CYCLE TIMING (See Notes 1 and 2)

Parameter	Symbol	MCM67A618B-10		Unit	Notes	
		Min	Max			
Read Cycle Times	$t_{AVAV}$	10	—	ns	3	
Access Times:	Address Valid to Output Valid	$t_{AVQV}$	—	10	ns	4
	$\bar{E}$ Low to Output Valid	$t_{ELQV}$	—	10		
	Output Enable Low to Output Valid	$t_{GLQV}$	—	5		
Output Hold from Address Change	$t_{AXQX}$	4	—	ns		
Output Buffer Control:	$\bar{E}$ Low to Output Active	$t_{ELQX}$	3	—	ns	5
	$\bar{G}$ Low to Output Active	$t_{GLQX}$	1	—		
	$\bar{E}$ High to Output High-Z	$t_{EHQZ}$	2	5		
	$\bar{G}$ High to Output High-Z	$t_{GHQZ}$	2	5		
Power Up Time	$t_{ELICCA}$	0	—	ns		


**NOTES:**

1. AL and DL are equal to  $V_{IH}$  for all asynchronous cycles.
2. Both Write Enable signals ( $\bar{LW}$ ,  $\bar{UW}$ ) are equal to  $V_{IH}$  for all read cycles.
3. All read cycle timing is referenced from the last valid address to the first transitioning address.
4. Addresses valid prior to or coincident with  $\bar{E}$  going low.
5. Transition is measured  $\pm 500$  mV from steady-state voltage. This parameter is sampled and not 100% tested. At any given voltage and temperature,  $t_{EHQZ}$  is less than  $t_{ELQX}$  and  $t_{GHQZ}$  is less than  $t_{GLQX}$  for a given device.



**Figure 1. AC Test Load**

**ASYNCHRONOUS READ CYCLES**



Freescale Semiconductor, Inc.

ARCHIVED BY FREESCALE SEMICONDUCTOR, INC.


## ASYNCHRONOUS WRITE CYCLE TIMING (See Notes 1, 2, and 3)

Parameter	Symbol	MCM67A618B-10		Unit	Notes
		Min	Max		
Write Cycle Times	$t_{AVAV}$	10	—	ns	4
Setup Times:	Address Valid to End of Write	$t_{AVWH}$	9	—	ns
	Address Valid to $\bar{E}$ High	$t_{AVEH}$	9	—	
	Address Valid to $\bar{W}$ Low	$t_{AVWL}$	0	—	
	Address Valid to $\bar{E}$ Low	$t_{AVEL}$	0	—	
	Data Valid to $\bar{W}$ High	$t_{DVWH}$	5	—	
	Data Valid $\bar{E}$ High	$t_{DVEH}$	5	—	
Hold Times:	$\bar{W}$ High to Address Invalid	$t_{WHAX}$	0	—	ns
	$\bar{E}$ High to Address Invalid	$t_{EHAX}$	0	—	
	$\bar{W}$ High to Data Invalid	$t_{WHDX}$	0	—	
	$\bar{E}$ High to Data Invalid	$t_{EHDX}$	0	—	
Write Pulse Width:	Write Pulse Width ( $\bar{G}$ Low)	$t_{WLWH}$	9	—	ns
	Write Pulse Width ( $\bar{G}$ High)	$t_{WLWH}$	8	—	
	Write Pulse Width	$t_{WLEH}$	9	—	5
	Enable to End of Write	$t_{ELWH}$	9	—	6
	Enable to End of Write	$t_{ELEH}$	9	—	5, 6
Output Buffer Control:	$\bar{W}$ High to Output Active	$t_{WHQX}$	3	—	ns
	$\bar{W}$ Low to Output High-Z	$t_{WLQZ}$	—	5	7, 8

### NOTES:

1. In setup and hold times, W (write) refers to either one or both byte write enables  $\bar{LW}$  and  $\bar{UW}$ .
2. AL and DL are equal to  $V_{IH}$  for all asynchronous cycles.
3. Both Write Enables must be equal to  $V_{IH}$  for all address transitions.
4. All write cycle timing is referenced from the last valid address to the first transitioning address.
5. If  $\bar{E}$  goes high coincident with or before  $\bar{W}$  goes high the output will remain in a high-impedance state.
6. If  $\bar{E}$  goes low coincident with or after  $\bar{W}$  goes low the output will remain in a high-impedance state.
7. Transition is measured  $\pm 500$  mV from steady-state voltage. This parameter is sampled and not 100% tested. At any given voltage and temperature,  $t_{WLQZ}$  is less than  $t_{WHQX}$  for a given device.
8. If  $\bar{G}$  goes low coincident with or after  $\bar{W}$  goes low the output will remain in a high impedance state.

**ASYNCHRONOUS WRITE CYCLE**



Freescale Semiconductor, Inc.

ARCHIVED BY FREESCALE SEMICONDUCTOR, INC.


## LATCHED READ CYCLE TIMING (See Notes 1 and 2)

Parameter	Symbol	MCM67A618B-10		Unit	Notes	
		Min	Max			
Read Cycle Times	$t_{AVAV}$	10	—	ns	3	
Access Times:	Address Valid to Output Valid	$t_{AVQV}$	—	10	ns	3
	$\bar{E}$ Low to Output Valid	$t_{ELQV}$	—	10		4
	AL High to Output Valid	$t_{ALHQV}$	—	10		
	Output Enable Low to Output Valid	$t_{GLQV}$	—	5		
Setup Times:	Address Valid to AL Low	$t_{AVALL}$	2	—	ns	4
	$\bar{E}$ Valid to AL Low	$t_{EVALL}$	2	—		4
	Address Valid to AL High	$t_{AVALH}$	0	—		
	$\bar{E}$ Valid to AL High	$t_{EVALH}$	0	—		
Hold Times:	AL Low to Address Invalid	$t_{ALLAX}$	2	—	ns	4
	AL Low to $\bar{E}$ Invalid	$t_{ALLEX}$	2	—		
Output Hold:	Address Invalid to Output Invalid	$t_{AXQX}$	4	—	ns	
	AL High to Output Invalid	$t_{ALHQX1}$	4	—		
Address Latch Pulse Width	$t_{ALHALL}$	5	—	ns		
Output Buffer Control:	$\bar{E}$ Low to Output Active	$t_{ELQX}$	3	—	ns	5
	$\bar{G}$ Low to Output Active	$t_{GLQX}$	1	—		
	AL High to Output Active	$t_{ALHQX2}$	3	—		
	$\bar{E}$ High to Output High-Z	$t_{EHQZ}$	2	5		
	AL High to Output High-Z	$t_{ALHQZ}$	2	5		
	$\bar{G}$ High to Output High-Z	$t_{GHQZ}$	2	5		

### NOTES:

- Both Write Enable Signals ( $\bar{LW}$ ,  $\bar{UW}$ ) are equal to  $V_{IH}$  for all read cycles.
- All read cycle timing is referenced from the last valid address to the first transitioning address.
- Addresses valid prior to or coincident with  $\bar{E}$  going low.
- All latched inputs must meet the specified setup and hold times with stable logic levels for ALL falling edges of address latch (AL) and data latch (DL).
- Transition is measured  $\pm 500$  mV from steady-state voltage. This parameter is sampled and not 100% tested. At any given voltage and temperature,  $t_{EHQZ}$  is less than  $t_{ELQX}$  and  $t_{ALHQZ}$  is less than  $t_{ALHQX2}$  and  $t_{GHQZ}$  is less than  $t_{GLQX}$  for a given device.

LATCHED READ CYCLES



Freescale Semiconductor, Inc.


## LATCHED WRITE CYCLE TIMING (See Notes 1, 2, and 3)

Parameter	Symbol	MCM67A618B-10		Unit	Notes
		Min	Max		
Write Cycle Times: Address Valid to Address Valid	$t_{AVAV}$	10	—	ns	4
Setup Times:	Address Valid to End of Write	$t_{AVWH}$	9	—	ns
	Address Valid to End of Write	$t_{AVEH}$	9	—	
	$\bar{E}$ Valid to AL Low	$t_{EVALL}$	2	—	
	Address Valid to AL Low	$t_{AVALL}$	2	—	
	$\bar{E}$ Valid to AL High	$t_{EVALH}$	0	—	
	Address Valid to AL High	$t_{AVALH}$	0	—	
	AL High to $\bar{W}$ Low	$t_{ALHWL}$	0	—	
	Address Valid to $\bar{W}$ Low	$t_{AVWL}$	0	—	
	Address Valid to $\bar{E}$ Low	$t_{AVEL}$	0	—	
	Data Valid to DL Low	$t_{DVDLL}$	2	—	
	Data Valid to $\bar{W}$ High	$t_{DVWH}$	5	—	
	Data Valid to $\bar{E}$ High	$t_{DVEH}$	5	—	
	DL High to $\bar{W}$ High	$t_{DLHWH}$	5	—	
DL High to $\bar{E}$ High	$t_{DLHEH}$	5	—		
Hold Times:	AL Low to $\bar{E}$ High	$t_{ALLEH}$	2	—	ns
	AL Low to Address Invalid	$t_{ALLAX}$	2	—	
	DL Low to Data Invalid	$t_{DLLDX}$	2	—	
	$\bar{W}$ High to Address Invalid	$t_{WHAX}$	0	—	
	$\bar{E}$ High to Address Invalid	$t_{EHAX}$	0	—	
	$\bar{W}$ High to Data Invalid	$t_{WHDX}$	0	—	
	$\bar{E}$ High to Data Invalid	$t_{EHDX}$	0	—	
	$\bar{W}$ High to DL High	$t_{WHDLH}$	0	—	
	$\bar{E}$ High to DL High	$t_{EHDHLH}$	0	—	
	$\bar{W}$ High to AL High	$t_{WHALH}$	0	—	
Write Pulse Width:	AL High to $\bar{W}$ High	$t_{ALHWH}$	9	—	ns
	Write Pulse Width ( $\bar{G}$ Low)	$t_{WLWH}$	9	—	
	Write Pulse Width ( $\bar{G}$ High)	$t_{WLWH}$	8	—	
	Write Pulse Width	$t_{WLEH}$	9	—	
	Enable to End of Write	$t_{ELWH}$	9	—	
	Enable to End of Write	$t_{ELEH}$	9	—	
Address Latch Pulse Width	$t_{ALHALL}$	5	—	ns	4
Output Buffer Control:	$\bar{W}$ High to Output Active	$t_{WHQX}$	3	—	ns
	$\bar{W}$ Low to Output High-Z	$t_{WLQZ}$	—	5	

### NOTES:

1. W (write) refers to either one or both byte write enables ( $\bar{LW}$ ,  $\bar{UW}$ ).
2. A write occurs during the overlap of  $\bar{E}$  low and  $\bar{W}$  low.
3. Both Write Enables must be equal to  $V_{IH}$  for all address transitions.
4. All write cycle timing is referenced from the last valid address to the first transitioning address.
5. All latched inputs must meet the specified setup and hold times with stable logic levels for ALL falling edges of address latch (AL) and data latch (DL).
6. If  $\bar{E}$  goes high coincident with or before  $\bar{W}$  goes high the output will remain in a high-impedance state.
7. If  $\bar{E}$  goes low coincident with or after  $\bar{W}$  goes low the output will remain in a high-impedance state.
8. Transition is measured  $\pm 500$  mV from steady-state voltage. This parameter is sampled and not 100% tested. At any given voltage and temperature,  $t_{WLQZ}$  is less than  $t_{WHQX}$  for a given device.
9. If  $\bar{G}$  goes low coincident with or after  $\bar{W}$  goes low the output will remain in a high impedance state.

LATCHED WRITE CYCLES



ORDERING INFORMATION  
(Order by Full Part Number)


**MCM 67A618B X XX**

Motorola Memory Prefix — **MCM**  
 Part Number — **67A618B**  
 Speed (10 = 10 ns) — **X**  
 Package (FN = PLCC) — **XX**

Full Part Numbers — MCM67A618BFN10

## PACKAGE DIMENSIONS

FN PACKAGE  
52-LEAD PLCC  
CASE 778-02



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.785	0.795	19.94	20.19
B	0.785	0.795	19.94	20.19
C	0.165	0.180	4.20	4.57
E	0.090	0.110	2.29	2.79
F	0.013	0.019	0.33	0.48
G	0.050 BSC		1.27 BSC	
H	0.026	0.032	0.66	0.81
J	0.020	—	0.51	—
K	0.025	—	0.64	—
R	0.750	0.756	19.05	19.20
U	0.750	0.756	19.05	19.20
V	0.042	0.048	1.07	1.21
W	0.042	0.048	1.07	1.21
X	0.042	0.056	1.07	1.42
Y	—	0.020	—	0.50
Z	2°	10°	2°	10°
G1	0.710	0.730	18.04	18.54
K1	0.040	—	1.02	—



ARCHIVED BY FREESCALE SEMICONDUCTOR, INC.



ARCHIVED BY FREESCALE SEMICONDUCTOR, INC.



ARCHIVED BY FREESCALE SEMICONDUCTOR, INC.



ARCHIVED BY FREESCALE SEMICONDUCTOR, INC.

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Mfax is a trademark of Motorola, Inc.

**How to reach us:**

**USA/EUROPE/ Locations Not Listed:** Motorola Literature Distribution; P.O. Box 5405, Denver, Colorado, 80217. 1-303-675-2140 or 1-800-441-2447

**Mfax™:** RMFAX0@email.sps.mot.com – TOUCHTONE 1-602-244-6609  
Motorola Fax Back System – US & Canada ONLY 1-800-774-1848  
– http://sps.motorola.com/mfax/

**HOME PAGE:** http://motorola.com/sps/

**JAPAN:** Motorola Japan Ltd.; SPS, Technical Information Center, 3-20-1, Minami-Azabu, Minato-ku, Tokyo 106-8573 Japan. 81-3-3440-3569

**ASIA/PACIFIC:** Motorola Semiconductors H.K. Ltd.; Silicon Harbour Centre, 2 Dai King Street, Tai Po Industrial Estate, Tao Po, N.T., Hong Kong. 852-26668334

**CUSTOMER FOCUS CENTER:** 1-800-521-6274



**MOTOROLA**

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**

MCM67A618B/D