

FEATURES

- Transceiver for Memory Card Interface [MultiMediaCard (MMC), Secure Digital (SD), Memory Stick™ Compliant Products]
- Configurable I/O Switching Levels With Dual-Supply Pins Operating Over Full 1.2-V to 3.6-V Power-Supply Range
- For Low-Power Operation, A and B Ports Are Placed in High-Impedance State When Either Supply Voltage Is Switched Off
- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Protection Exceeds JESD 22
 - 6000-V Human-Body Model (A114-A)
 - 200-V Machine Model (A115-A)
 - 1000-V Charged-Device Model (C101)

DESCRIPTION/ORDERING INFORMATION

The SN74AVCA406L is a transceiver for interfacing microprocessors with MultiMediaCards (MMCs), secure digital (SD) cards, and Memory Stick™ compliant products.

Two supply-voltage pins allow the A-port and B-port input switching thresholds to be configured separately. The A port is designed to track V_{CCA} , while the B port is designed to track V_{CCB} . V_{CCA} and V_{CCB} can accept any supply voltage from 1.2 V to 3.6 V.

If either V_{CC} is switched off ($V_{CCA} = 0$ V and/or $V_{CCB} = 0$ V), all outputs are placed in the high-impedance state to conserve power.

The SN74AVCA406L enables system designers to easily interface low-voltage microprocessors to different memory cards operating at higher voltages.

The SN74AVCA406L is available in two 0.5-mm-pitch ball grid array (BGA) packages. The 20-ball package has dimensions of 3 mm × 2.5 mm, and the 24-ball package measures 3 mm × 3 mm. Memory cards are widely used in mobile phones, PDAs, digital cameras, personal media players, camcorders, set-top boxes, etc. Low static power consumption and small package size make the SN74AVCA406L an ideal choice for these applications.

ORDERING INFORMATION

| T_A | PACKAGE ⁽¹⁾ | | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|---------------|---------------------------------------|--------------|-----------------------|------------------|
| –40°C to 85°C | UFBGA – GXY | Reel of 2500 | SN74AVCA406LGXYR | WV406 |
| | UFBGA – ZXY (Pb-Free) | Reel of 2500 | SN74AVCA406LZXYP | WV406 |
| | MicroStar Junior™ BGA – GQS | Reel of 2500 | SN74AVCA406LGQSR | WM406L |
| | MicroStar Junior™ BGA – ZQS (Pb-Free) | Reel of 2500 | SN74AVCA406LZQSR | WM406L |


(1) Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

MicroStar Junior is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

GXY OR ZXY PACKAGE
 (TOP VIEW)



GQS OR ZQS PACKAGE
 (TOP VIEW)



TERMINAL ASSIGNMENTS
 (20-Ball GXY/ZXY Package)

| | A | B | C | D |
|---|------------------|---------|------------|------------------|
| 5 | V _{CCA} | CMD-dir | DAT0-dir | V _{CCB} |
| 4 | DAT3A | DAT2A | DAT2B | DAT3B |
| 3 | CLKA | GND | GND | CLKB |
| 2 | DAT1A | DAT0A | CMDB | DAT0B |
| 1 | CLK-f | CMDA | DAT123-dir | DAT1B |

TERMINAL ASSIGNMENTS
 (24-Ball GQS/ZQS Package)

| | 1 | 2 | 3 | 4 | 5 |
|---|-------|---------|------------------|------------------|-------|
| A | DAT2A | CMD-dir | DAT0-dir | RSV | DAT2B |
| B | DAT3A | | V _{CCA} | V _{CCB} | DAT3B |
| C | CLKA | RSV | GND | GND | CLKB |
| D | DAT0A | CMDA | RSV | CMDB | DAT0B |
| E | DAT1A | CLK-f | DAT123-dir | RSV | DAT1B |

REFERENCE DESIGN




Figure 1. Interfacing With SD/SDIO Card

PIN DESCRIPTION

| GXY/ZXY NO. | GQS/ZQS NO. | NAME | FUNCTION | TYPE |
|-------------|----------------|------------|----------------------------------------------------------------------------------------------------------|--------|
| A1 | E2 | CLK-f | Clock feedback to host for resynchronizing data. Used in OMAP processors. Leave unconnected if not used. | Output |
| A2 | E1 | DAT1A | Data bit 2 connected to host. Referenced to V_{CCA} . | I/O |
| A3 | C1 | CLKA | Clock signal connected to host. Referenced to V_{CCA} . | Input |
| A4 | B1 | DAT3A | Data bit 4 connected to host. Referenced to V_{CCA} . | I/O |
| A5 | B3 | V_{CCA} | A-port supply voltage. V_{CCA} powers all A-port I/Os and control inputs. | Power |
| B1 | D2 | CMDA | Command bit connected to host. Referenced to V_{CCA} . | I/O |
| B2 | D1 | DAT0A | Data bit 1 connected to host. Referenced to V_{CCA} . | I/O |
| B3 | C4 | GND | Ground | |
| B4 | A1 | DAT2A | Data bit 3 connected to host. Referenced to V_{CCA} . | I/O |
| B5 | A2 | CMD-dir | Direction control for command bit (CMDA/CMDB) | Input |
| C1 | E3 | DAT123-dir | Direction control for DAT1A/B, DAT2A/B, and DAT3A/B | Input |
| C2 | D4 | CMDB | Command bit connected to memory card. Referenced to V_{CCB} . | I/O |
| C3 | C3 | GND | Ground | |
| C4 | A5 | DAT2B | Data bit 3 connected to memory card. Referenced to V_{CCB} . | I/O |
| C5 | A3 | DAT0-dir | Direction control for DAT0A/DAT0B | Input |
| D1 | E5 | DAT1B | Data bit 2 connected to memory card. Referenced to V_{CCB} . | I/O |
| D2 | D5 | DAT0B | Data bit 1 connected to memory card. Referenced to V_{CCB} . | I/O |
| D3 | C5 | CLKB | Clock signal connected to memory card. Referenced to V_{CCB} . | Output |
| D4 | B5 | DAT3B | Data bit 4 connected to memory card. Referenced to V_{CCB} . | I/O |
| D5 | B4 | V_{CCB} | B-port supply voltage. V_{CCB} powers all B-port I/Os. | Power |
| NA | B2 | | Depopulated ball | |
| NA | A4, C2, D3, E4 | RSV | Reserved (for possible future functionality). Leave unconnected. | |


FUNCTION TABLES

| CONTROL INPUT CMD-dir | OUTPUT CIRCUITS | | OPERATION |
|--------------------------|-----------------|---------|--------------|
| | CMDA | CMDB | |
| High | Hi-Z | Enabled | CMDA to CMDB |
| Low | Enabled | Hi-Z | CMDB to CMDA |

| CONTROL INPUT DAT0-dir | OUTPUT CIRCUITS | | FUNCTION |
|---------------------------|-----------------|---------|----------------|
| | DAT0A | DAT0B | |
| High | Hi-Z | Enabled | DAT0A to DAT0B |
| Low | Enabled | Hi-Z | DAT0B to DAT0A |

| CONTROL INPUT DAT123-dir | OUTPUT CIRCUITS | | FUNCTION |
|-----------------------------|---------------------------|---------------------------|----------------|
| | DAT1A, DAT2A, DAT3A | DAT1B, DAT2B, DAT3B | |
| High | Hi-Z | Enabled | DAT1A to DAT1B |
| | | | DAT2A to DAT2B |
| | | | DAT3A to DAT3B |
| Low | Enabled | Hi-Z | DAT1B to DAT1A |
| | | | DAT2B to DAT2A |
| | | | DAT3B to DAT3A |

LOGIC DIAGRAM (POSITIVE LOGIC)



Absolute Maximum Ratings⁽¹⁾

over operating free-air temperature range (unless otherwise noted)

| | | MIN | MAX | UNIT | |
|------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------|-------|-----------------|---|
| V_{CCA} V_{CCB} | Supply voltage range | –0.5 | 4.6 | V | |
| V_I | Input voltage range ⁽²⁾ | I/O ports (A port) | –0.5 | 4.6 | V |
| | | I/O ports (B port) | –0.5 | 4.6 | |
| | | Control inputs | –0.5 | 4.6 | |
| V_O | Voltage range applied to any output in the high-impedance or power-off state ⁽²⁾ | A port | –0.5 | 4.6 | V |
| | | B port | –0.5 | 4.6 | |
| V_O | Voltage range applied to any output in the high or low state ⁽²⁾⁽³⁾ | A port | –0.5 | $V_{CCA} + 0.5$ | V |
| | | B port | –0.5 | $V_{CCB} + 0.5$ | |
| I_{IK} | Input clamp current | $V_I < 0$ | –50 | mA | |
| I_{OK} | Output clamp current | $V_O < 0$ | –50 | mA | |
| I_O | Continuous output current | | ±50 | mA | |
| | | Continuous current through V_{CCA} , V_{CCB} , or GND | ±100 | mA | |
| θ_{JA} | Package thermal impedance ⁽⁴⁾ | GQS/ZQS package | 171.6 | °C/W | |
| | | GXY/ZXY package | 193 | | |
| T_{stg} | Storage temperature range | –65 | 150 | °C | |

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input voltage and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.
- (3) The output positive-voltage rating may be exceeded up to 4.6 V maximum if the output current rating is observed.
- (4) The package thermal impedance is calculated in accordance with JESD 51-7.

Recommended Operating Conditions⁽¹⁾⁽²⁾⁽³⁾

| | | V_{CCI} | V_{CCO} | MIN | MAX | UNIT |
|---------------------|------------------------------------|---------------------------|------------------|-----------------------|-----------|------|
| V_{CCA} | Supply voltage | | | 1.2 | 3.6 | V |
| V_{CCB} | Supply voltage | | | 1.2 | 3.6 | V |
| V_{IH} | High-level input voltage | All inputs ⁽⁴⁾ | 1.2 V to 1.95 V | $V_{CCI} \times 0.65$ | | V |
| | | | 1.95 V to 2.7 V | 1.7 | | |
| | | | 2.7 V to 3.6 V | 2 | | |
| V_{IL} | Low-level input voltage | All inputs ⁽⁴⁾ | 1.2 V to 1.95 V | $V_{CCI} \times 0.35$ | | V |
| | | | 1.95 V to 2.7 V | 0.7 | | |
| | | | 2.7 V to 3.6 V | 0.8 | | |
| V_I | Input voltage | Control inputs | | 0 | 3.6 | V |
| V_{IO} | Input/output voltage | Active state | | 0 | V_{CCO} | V |
| | | 3-state | | 0 | 3.6 | |
| I_{OH} | High-level output current (A port) | | 1.2 V | –1 | | mA |
| | | | 1.4 V to 1.6 V | –1 | | |
| | | | 1.65 V to 1.95 V | –2 | | |
| | | | 2.3 V to 2.7 V | –4 | | |
| | | | 3 V to 3.6 V | –8 | | |
| I_{OL} | Low-level output current (A port) | | 1.2 V | 1 | | mA |
| | | | 1.4 V to 1.6 V | 1 | | |
| | | | 1.65 V to 1.95 V | 2 | | |
| | | | 2.3 V to 2.7 V | 4 | | |
| | | | 3 V to 3.6 V | 8 | | |
| I_{OH} | High-level output current (B port) | | 1.2 V | –1 | | mA |
| | | | 1.4 V to 1.6 V | –2 | | |
| | | | 1.65 V to 1.95 V | –4 | | |
| | | | 2.3 V to 2.7 V | –8 | | |
| | | | 3 V to 3.6 V | –16 | | |
| I_{OL} | Low-level output current (B port) | | 1.2 V | 1 | | mA |
| | | | 1.4 V to 1.6 V | 2 | | |
| | | | 1.65 V to 1.95 V | 4 | | |
| | | | 2.3 V to 2.7 V | 8 | | |
| | | | 3 V to 3.6 V | 16 | | |
| $\Delta t/\Delta v$ | Input transition rise or fall rate | | | | 5 | ns/V |
| T_A | Operating free-air temperature | | | –40 | 85 | °C |

- (1) V_{CCI} is the V_{CC} associated with the input port.
- (2) V_{CCO} is the V_{CC} associated with the output port.
- (3) All unused data inputs of the device must be held at V_{CCI} or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.
- (4) CMD-dir, DAT0-dir, and DAT123-dir are referenced to V_{CCA} .

Electrical Characteristics⁽¹⁾⁽²⁾

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | V _{CCA} | V _{CCB} | T _A = 25°C | | | UNIT |
|-------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|-----------------------------------------------------------|------------------|------------------|------------------------|--------------------|-----|------|
| | | | | | | MIN | TYP ⁽³⁾ | MAX | |
| V _{OH} | A port | I _{OH} = –100 μA | V _I = V _{IH} | 1.2 V to 3.6 V | 1.2 V to 3.6 V | V _{CCO} – 0.2 | | | V |
| | | I _{OH} = –1 mA | | 1.2 V | 1.2 V | 1.1 | | | |
| | | I _{OH} = –2 mA | | 1.4 V | 1.4 V | 1.05 | | | |
| | | I _{OH} = –4 mA | | 1.65 V | 1.65 V | 1.2 | | | |
| | | I _{OH} = –8 mA | | 2.3 V | 2.3 V | 1.75 | | | |
| | | I _{OH} = –8 mA | | 3 V | 3 V | 2.3 | | | |
| V _{OL} | A port | I _{OL} = 100 μA | V _I = V _{IL} | 1.2 V to 3.6 V | 1.2 V to 3.6 V | 0.2 | | | V |
| | | I _{OL} = 1 mA | | 1.2 V | 1.2 V | 0.07 | | | |
| | | I _{OL} = 2 mA | | 1.4 V | 1.4 V | 0.35 | | | |
| | | I _{OL} = 4 mA | | 1.65 V | 1.65 V | 0.45 | | | |
| | | I _{OL} = 8 mA | | 2.3 V | 2.3 V | 0.55 | | | |
| | | I _{OL} = 8 mA | | 3 V | 3 V | 0.7 | | | |
| V _{OH} | B port | I _{OH} = –100 μA | V _I = V _{IH} | 1.2 V to 3.6 V | 1.2 V to 3.6 V | V _{CCO} – 0.2 | | | V |
| | | I _{OH} = –1 mA | | 1.2 V | 1.2 V | 1.1 | | | |
| | | I _{OH} = –2 mA | | 1.4 V | 1.4 V | 1.05 | | | |
| | | I _{OH} = –4 mA | | 1.65 V | 1.65 V | 1.2 | | | |
| | | I _{OH} = –8 mA | | 2.3 V | 2.3 V | 1.75 | | | |
| | | I _{OH} = –16 mA | | 3 V | 3 V | 2.3 | | | |
| V _{OL} | B port | I _{OL} = 100 μA | V _I = V _{IL} | 1.2 V to 3.6 V | 1.2 V to 3.6 V | 0.2 | | | V |
| | | I _{OL} = 1 mA | | 1.2 V | 1.2 V | 0.07 | | | |
| | | I _{OL} = 2 mA | | 1.4 V | 1.4 V | 0.35 | | | |
| | | I _{OL} = 4 mA | | 1.65 V | 1.65 V | 0.45 | | | |
| | | I _{OL} = 8 mA | | 2.3 V | 2.3 V | 0.55 | | | |
| | | I _{OL} = 16 mA | | 3 V | 3 V | 0.7 | | | |
| I _I | Control inputs | V _I = V _{CCA} or GND | | 1.2 V to 3.6 V | 1.2 V to 3.6 V | ±1 | | | μA |
| I _{off} | A or B port | V _I or V _O = 0 to 3.6 V | | 0 V | 0 V to 3.6 V | ±5 | | | μA |
| | | | | 0 V to 3.6 V | 0 V | ±5 | | | |
| I _{OZ} ⁽⁴⁾ | A or B port | V _O = V _{CCO} or GND, V _I = V _{CCI} or GND | See function table for input states when outputs are Hi Z | 3.6 V | 3.6 V | ±5 | | | μA |
| I _{CCA} | V _I = V _{CCI} or GND, I _O = 0 | | 1.2 V to 3.6 V | | 1.2 V to 3.6 V | 10 | | | μA |
| | | | 3.6 V | | 0 V | 10 | | | |
| | | | 0 V | | 3.6 V | –1 | | | |
| I _{CCB} | V _I = V _{CCI} or GND, I _O = 0 | | 1.2 V to 3.6 V | | 1.2 V to 3.6 V | 10 | | | μA |
| | | | 3.6 V | | 0 V | –1 | | | |
| | | | 0 V | | 3.6 V | 10 | | | |
| I _{CCA} + I _{CCB} | V _I = V _{CCI} or GND, I _O = 0 | | 1.2 V to 3.6 V | 1.2 V to 3.6 V | 15 | | | μA | |
| C _i | Control inputs | V _I = V _{CCA} or GND | | 1.8 V | 3 V | 1.5 | | 2 | pF |
| | Clock input | | | | | 2 | | | |
| C _{io} | A port | V _O = V _{CCA} or GND | | 1.8 V | 3 V | 2.5 | | 3 | pF |
| | B port | V _O = V _{CCB} or GND | | | | 2.5 | | | |

(1) V_{CCO} is the V_{CC} associated with the output port.(2) V_{CCI} is the V_{CC} associated with the input port.(3) All typical values are at T_A = 25°C.(4) For I/O ports, the parameter I_{OZ} includes the input leakage current.

Output Slew Rates⁽¹⁾

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | FROM | TO | $V_{CCA} = 1.8 V \pm 0.15 V$, $V_{CCB} = 3 V \pm 0.3 V$ | | UNIT |
|-----------|------|-----|-------------------------------------------------------------|-----|------|
| | | | MIN | MAX | |
| t_r | 10% | 90% | 3 ⁽²⁾ | | ns |
| t_f | 90% | 10% | 3 ⁽²⁾ | | ns |

- (1) Values are characterized, but not production tested.
(2) Using $C_L = 15$ pF on the B side and $C_L = 7$ pF on the A side

Typical Switching Characteristics

$T_A = 25^\circ C$, $V_{CCA} = 1.2 V$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 V$ | $V_{CCB} = 1.5 V$ | $V_{CCB} = 1.8 V$ | $V_{CCB} = 2.5 V$ | $V_{CCB} = 3 V$ | $V_{CCB} = 3.3 V$ | UNIT |
|-----------------|--------------|-------------|-------------------|-------------------|-------------------|-------------------|-----------------|-------------------|------|
| | | | TYP | TYP | TYP | TYP | TYP | TYP | |
| t_{pd} | A | B | 3.8 | 3 | 2.6 | 2.5 | 2.5 | 2.6 | ns |
| | B | A | 4.6 | 4.2 | 4 | 3.9 | 3.9 | 3.8 | |
| | CLKA | CLKB | 3.8 | 3 | 2.6 | 2.5 | 2.5 | 2.6 | |
| | | CLK-f | 8.4 | 7.2 | 6.6 | 6.4 | 6.4 | 6.4 | |
| | CMDA | CMDB | 3.8 | 3 | 2.6 | 2.5 | 2.5 | 2.6 | |
| CMDB | CMDA | 4.6 | 4.2 | 4 | 3.9 | 3.9 | 3.8 | | |
| $t_{en}^{(1)}$ | DIR | B | 4.8 | 4 | 3.7 | 3.4 | 3.4 | 3.4 | ns |
| | | A | 4.5 | 4.4 | 5 | 5.4 | 5.4 | 5.4 | |
| $t_{dis}^{(1)}$ | DIR | B | 6.3 | 5.2 | 5.6 | 4.8 | 4.8 | 6.1 | ns |
| | | A | 4.8 | 4.6 | 5.3 | 5.4 | 5.4 | 5.3 | |

- (1) DIR refers to CMD-dir, DAT0-dir, and DAT123-dir.

Switching Characteristics

over recommended operating free-air temperature range, $V_{CCA} = 1.5 V \pm 0.1 V$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 V$ | $V_{CCB} = 1.5 V \pm 0.1 V$ | | $V_{CCB} = 1.8 V \pm 0.15 V$ | | $V_{CCB} = 2.5 V \pm 0.2 V$ | | $V_{CCB} = 3 V \pm 0.3 V$ | | $V_{CCB} = 3.3 V \pm 0.3 V$ | | UNIT |
|-----------------|--------------|-------------|-------------------|-----------------------------|------|------------------------------|------|-----------------------------|-----|---------------------------|-----|-----------------------------|------|------|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | |
| t_{pd} | A | B | 3.4 | 1.1 | 5.6 | 1 | 4.8 | 1 | 3.9 | 0.9 | 3.9 | 0.9 | 3.8 | ns |
| | B | A | 3.8 | 1.4 | 6 | 1.3 | 5.6 | 1.3 | 5.2 | 0.5 | 5.2 | 0.3 | 5.2 | |
| | CLKA | CLKB | 3.4 | 1.1 | 5.6 | 1 | 4.8 | 1 | 3.9 | 0.9 | 3.9 | 0.9 | 3.8 | |
| | | CLK-f | 7.2 | 2.6 | 11.6 | 2.3 | 10.4 | 2.3 | 9.1 | 1.3 | 9.1 | 1.2 | 9 | |
| | CMDA | CMDB | 3.4 | 1.1 | 5.6 | 1 | 4.8 | 1 | 3.9 | 0.9 | 3.9 | 0.9 | 3.8 | |
| CMDB | CMDA | 3.8 | 1.4 | 6 | 1.3 | 5.6 | 1.3 | 5.2 | 0.5 | 5.2 | 0.3 | 5.2 | | |
| $t_{en}^{(1)}$ | DIR | B | 4 | 1.3 | 7.7 | 1.1 | 6.9 | 0.8 | 6.1 | 0.8 | 6 | 0.8 | 5.9 | ns |
| | | A | 3.5 | 1.4 | 7 | 1.5 | 7.4 | 1.7 | 8.2 | 1.7 | 8.2 | 1.7 | 7.7 | |
| $t_{dis}^{(1)}$ | DIR | B | 5.7 | 1.9 | 8.9 | 2.1 | 10.4 | 1.8 | 8.7 | 1.7 | 8.5 | 2.4 | 11.4 | ns |
| | | A | 3.4 | 1.2 | 7 | 1.2 | 6.8 | 1.2 | 6.9 | 1.2 | 6.5 | 1.2 | 6.6 | |

- (1) DIR refers to CMD-dir, DAT0-dir, and DAT123-dir.

Switching Characteristics

over recommended operating free-air temperature range, $V_{CCA} = 1.8 \text{ V} \pm 0.15 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ | | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ | | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ | | $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$ | | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ | | UNIT |
|-----------------|--------------|-------------|---------------------------|---------------------------------------------|------|----------------------------------------------|-----|---------------------------------------------|-----|-------------------------------------------|-----|---------------------------------------------|-----|------|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | |
| t_{pd} | A | B | 3.2 | 1 | 5.2 | 0.8 | 4.4 | 0.7 | 3.5 | 0.6 | 3.4 | 0.7 | 3.1 | ns |
| | | A | 3.4 | 1.1 | 5.2 | 1 | 4.8 | 0.9 | 4.3 | 0.3 | 4.3 | 0.2 | 4.3 | |
| | CLKA | CLKB | 3.2 | 1 | 5.2 | 0.8 | 4.4 | 0.7 | 3.5 | 0.6 | 3.4 | 0.7 | 3.1 | |
| | | CLK-f | 6.5 | 2.1 | 10.4 | 1.8 | 9.1 | 1.7 | 7.8 | 0.9 | 7.7 | 0.9 | 7.4 | |
| | CMDA | CMDB | 3.2 | 1 | 5.2 | 0.8 | 4.4 | 0.7 | 3.5 | 0.6 | 3.4 | 0.7 | 3.1 | |
| CMDB | CMDA | 3.4 | 1.1 | 5.2 | 1 | 4.8 | 0.9 | 4.3 | 0.3 | 4.3 | 0.2 | 4.3 | | |
| $t_{en}^{(1)}$ | DIR | B | 3.5 | 1.2 | 6.8 | 0.9 | 6 | 0.7 | 5.1 | 0.7 | 5 | 0.7 | 4.8 | ns |
| | | A | 2.9 | 1.1 | 4.7 | 1.1 | 5.2 | 1.4 | 5.1 | 1.4 | 5.1 | 1.4 | 5.3 | |
| $t_{dis}^{(1)}$ | DIR | B | 5.3 | 1.6 | 8.4 | 2 | 9.5 | 1.6 | 8.2 | 1.4 | 8.1 | 2.2 | 8.2 | ns |
| | | A | 3.6 | 1.3 | 7.7 | 1.2 | 7.9 | 1.3 | 7.5 | 1.3 | 7.5 | 1.3 | 7.6 | |

(1) DIR refers to CMD-dir, DAT0-dir, and DAT123-dir.

Switching Characteristics

over recommended operating free-air temperature range, $V_{CCA} = 2.5 \text{ V} \pm 0.2 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ | | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ | | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ | | $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$ | | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ | | UNIT |
|----------------|--------------|-------------|---------------------------|---------------------------------------------|-----|----------------------------------------------|-----|---------------------------------------------|-----|-------------------------------------------|-----|---------------------------------------------|-----|------|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | |
| t_{pd} | A | B | 3 | 0.8 | 4.7 | 0.7 | 3.8 | 0.6 | 2.9 | 0.4 | 2.7 | 0.5 | 2.5 | ns |
| | | A | 3 | 0.9 | 4.4 | 0.7 | 3.9 | 0.6 | 3.3 | 0.3 | 3.2 | 0.3 | 3.2 | |
| | CLKA | CLKB | 3 | 0.8 | 4.7 | 0.7 | 3.8 | 0.6 | 2.9 | 0.4 | 2.7 | 0.5 | 2.5 | |
| | | CLK-f | 6 | 1.7 | 9.1 | 1.4 | 7.7 | 1.1 | 6.2 | 0.7 | 5.9 | 0.8 | 5.7 | |
| | CMDA | CMDB | 3 | 0.8 | 4.7 | 0.7 | 3.8 | 0.6 | 2.9 | 0.4 | 2.7 | 0.5 | 2.5 | |
| CMDB | CMDA | 3 | 0.9 | 4.4 | 0.7 | 3.9 | 0.6 | 3.3 | 0.3 | 3.2 | 0.3 | 3.2 | | |
| $t_{en}^{(1)}$ | DIR | B | 3.1 | 1 | 5.7 | 0.8 | 4.8 | 0.5 | 3.9 | 0.5 | 3.7 | 0.5 | 3.6 | ns |
| | | A | 2.2 | 0.7 | 3.5 | 0.6 | 4.3 | 1.2 | 4.4 | 0.7 | 4.6 | 0.4 | 4.7 | |
| t_{dis} | DIR | B | 4.6 | 1.4 | 7.6 | 1.8 | 8.4 | 1.3 | 7.2 | 1.3 | 7.1 | 2 | 7.5 | ns |
| | | A | 2.6 | 0.9 | 5.6 | 0.9 | 5.4 | 1 | 5.5 | 0.9 | 5.5 | 0.9 | 5.8 | |

(1) DIR refers to CMD-dir, DAT0-dir, and DAT123-dir.

Switching Characteristics

over recommended operating free-air temperature range, $V_{CCA} = 3.3 \text{ V} \pm 0.3 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ | | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ | | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ | | $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$ | | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ | | UNIT |
|-----------------|--------------|-------------|---------------------------|---------------------------------------------|-----|----------------------------------------------|-----|---------------------------------------------|-----|-------------------------------------------|-----|---------------------------------------------|-----|------|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | |
| t_{pd} | A | B | 2.8 | 0.8 | 4.5 | 0.6 | 3.6 | 0.4 | 2.7 | 0.4 | 2.7 | 0.3 | 2.3 | ns |
| | | A | 2.9 | 0.8 | 4.3 | 0.6 | 3.7 | 0.5 | 3 | 0.5 | 3 | 0.1 | 2.7 | |
| | CLKA | CLKB | 2.8 | 0.8 | 4.5 | 0.6 | 3.6 | 0.4 | 2.7 | 0.4 | 2.7 | 0.3 | 2.3 | |
| | | CLK-f | 5.7 | 1.6 | 8.8 | 1.2 | 7.3 | 0.9 | 5.7 | 0.9 | 5.7 | 0.4 | 5 | |
| | CMDA | CMDB | 2.8 | 0.8 | 4.5 | 0.6 | 3.6 | 0.4 | 2.7 | 0.4 | 2.7 | 0.3 | 2.3 | |
| CMDB | CMDA | 2.9 | 0.8 | 4.3 | 0.6 | 3.7 | 0.5 | 3 | 0.5 | 3 | 0.1 | 2.7 | | |
| $t_{en}^{(1)}$ | DIR | B | 3 | 1 | 5.1 | 0.6 | 4.3 | 0.5 | 3.4 | 0.5 | 3.4 | 0.4 | 3 | ns |
| | | A | 2 | 0.6 | 3.1 | 0.6 | 5.4 | 0.7 | 5.4 | 0.7 | 5.4 | 0.5 | 5.4 | |
| $t_{dis}^{(1)}$ | DIR | B | 4.4 | 1.4 | 7.4 | 1.8 | 8.3 | 1.2 | 7 | 1.2 | 7 | 2 | 7.3 | ns |
| | | A | 3.7 | 1.5 | 8.1 | 1.5 | 7.9 | 1.5 | 7.9 | 1.5 | 7.9 | 1.5 | 8 | |

(1) DIR refers to CMD-dir, DAT0-dir, and DAT123-dir.

Typical Frequency and Output Skew

$T_A = 25^\circ\text{C}$, $V_{CCA} = 1.2 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V}$ | $V_{CCB} = 1.8 \text{ V}$ | $V_{CCB} = 2.5 \text{ V}$ | $V_{CCB} = 3 \text{ V}$ | $V_{CCB} = 3.3 \text{ V}$ | UNIT | |
|-------------|--------------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|-------------------------|---------------------------|------|----|
| | | | TYP | TYP | TYP | TYP | TYP | TYP | | |
| t_{max} | Clock | CLKA | 95 | 95 | 95 | 95 | 95 | 95 | MHz | |
| | | CLK-f | 95 | 95 | 95 | 95 | 95 | 95 | | |
| | Data | A | 95 | 95 | 95 | 95 | 95 | 95 | | |
| | | B | 95 | 95 | 95 | 95 | 95 | 95 | | |
| $t_{sk(o)}$ | Channel to channel | A | B | 0.5 | 0.4 | 0.4 | 0.3 | 0.5 | 0.5 | ns |

Maximum Frequency and Output Skew

over recommended operating free-air temperature range, $V_{CCA} = 1.5 \text{ V} \pm 0.1 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ | | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ | | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ | | $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$ | | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ | | UNIT |
|-------------|--------------------|-------------|---------------------------|---------------------------------------------|-----|----------------------------------------------|-----|---------------------------------------------|-----|-------------------------------------------|-----|---------------------------------------------|-----|------|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | |
| f_{max} | Clock | CLKA | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | MHz | |
| | | CLK-f | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | |
| | Data | A | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | |
| | | B | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | |
| $t_{sk(o)}$ | Channel to channel | DIR | B | 0.3 | 0.3 | 0.3 | 0.3 | 0.3 | 0.5 | 0.4 | 0.4 | ns | | |

Maximum Frequency and Output Skewover recommended operating free-air temperature range, $V_{CCA} = 1.8 \text{ V} \pm 0.15 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ | | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ | | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ | | $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$ | | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ | | UNIT | |
|-------------|--------------------|-------------|---------------------------|---------------------------------------------|-----|----------------------------------------------|-----|---------------------------------------------|-----|-------------------------------------------|-----|---------------------------------------------|-----|------|----|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | | |
| f_{\max} | Clock | CLKA | CLKB | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | MHz | | |
| | | | CLK-f | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| | Data | A | B | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| | | B | A | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| $t_{sk(o)}$ | Channel to channel | DIR | B | 0.3 | | 0.3 | | 0.3 | | 0.3 | | 0.5 | | 0.3 | ns |

Maximum Frequency and Output Skewover recommended operating free-air temperature range, $V_{CCA} = 2.5 \text{ V} \pm 0.2 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ | | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ | | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ | | $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$ | | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ | | UNIT | |
|-------------|--------------------|-------------|---------------------------|---------------------------------------------|-----|----------------------------------------------|-----|---------------------------------------------|-----|-------------------------------------------|-----|---------------------------------------------|-----|------|----|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | | |
| f_{\max} | Clock | CLKA | CLKB | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | MHz | | |
| | | | CLK-f | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| | Data | A | B | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| | | B | A | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| $t_{sk(o)}$ | Channel to channel | DIR | B | 0.3 | | 0.3 | | 0.3 | | 0.2 | | 0.6 | | 0.3 | ns |

Maximum Frequency and Output Skewover recommended operating free-air temperature range, $V_{CCA} = 3.3 \text{ V} \pm 0.3 \text{ V}$ (see Figure 2)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ | | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ | | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ | | $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$ | | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ | | UNIT | |
|-------------|--------------------|-------------|---------------------------|---------------------------------------------|-----|----------------------------------------------|-----|---------------------------------------------|-----|-------------------------------------------|-----|---------------------------------------------|-----|------|----|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | | |
| f_{\max} | Clock | CLKA | CLKB | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | MHz | | |
| | | | CLK-f | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| | Data | A | B | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| | | B | A | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | | |
| $t_{sk(o)}$ | Channel to channel | DIR | B | 0.3 | | 0.3 | | 0.4 | | 0.3 | | 0.6 | | 0.4 | ns |


Operating Characteristics

$T_A = 25^\circ\text{C}$

| PARAMETER | | TEST CONDITIONS | $V_{CCA} =$ $V_{CCB} = 1.2\text{ V}$ | $V_{CCA} =$ $V_{CCB} = 1.5\text{ V}$ | $V_{CCA} =$ $V_{CCB} = 1.8\text{ V}$ | $V_{CCA} =$ $V_{CCB} = 2.5\text{ V}$ | $V_{CCA} =$ $V_{CCB} = 3\text{ V}$ | $V_{CCA} =$ $V_{CCB} = 3.3\text{ V}$ | UNIT |
|-----------------|-----------------------------|-----------------------------------------------------------------|-----------------------------------------|-----------------------------------------|-----------------------------------------|-----------------------------------------|---------------------------------------|-----------------------------------------|------|
| | | | TYP | TYP | TYP | TYP | TYP | TYP | |
| $C_{pdA}^{(1)}$ | A-port input, B-port output | $C_L = 0,$ $f = 10\text{ MHz},$ $t_r = t_f = 1\text{ ns}$ | 1.9 | 2 | 2.1 | 2.4 | 2.7 | 2.9 | pF |
| | B-port input, A-port output | | 4.4 | 4.5 | 4.6 | 4.7 | 4.8 | 4.9 | |
| $C_{pdB}^{(1)}$ | A-port input, B-port output | $C_L = 0,$ $f = 10\text{ MHz},$ $t_r = t_f = 1\text{ ns}$ | 5.3 | 5.4 | 5.4 | 5.7 | 5.8 | 5.9 | pF |
| | B-port input, A-port output | | 0.3 | 0.3 | 0.4 | 0.5 | 0.6 | 0.6 | |


(1) Power dissipation capacitance per transceiver

PARAMETER MEASUREMENT INFORMATION



| TEST | S1 |
|-------------------|--------------------|
| t_{pd} | Open |
| t_{PLZ}/t_{PZL} | $2 \times V_{CCO}$ |
| t_{PHZ}/t_{PZH} | GND |

| V_{CCO} | C_L | R_L | V_{TP} |
|------------------------------------|-------|--------------|----------|
| $1.5 \text{ V} \pm 0.1 \text{ V}$ | 15 pF | 2 k Ω | 0.1 V |
| $1.8 \text{ V} \pm 0.15 \text{ V}$ | 15 pF | 2 k Ω | 0.15 V |
| $2.5 \text{ V} \pm 0.2 \text{ V}$ | 15 pF | 2 k Ω | 0.15 V |
| $3.3 \text{ V} \pm 0.3 \text{ V}$ | 15 pF | 2 k Ω | 0.3 V |



- NOTES:
- A. C_L includes probe and jig capacitance.
 - B. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
 - C. All input pulses are supplied by generators having the following characteristics: $PRR \leq 10 \text{ MHz}$, $Z_O = 50 \Omega$, $dv/dt \geq 1 \text{ V/ns}$.
 - D. The outputs are measured one at a time, with one transition per measurement.
 - E. t_{PLZ} and t_{PHZ} are the same as t_{dis} .
 - F. t_{PZL} and t_{PZH} are the same as t_{en} .
 - G. t_{PLH} and t_{PHL} are the same as t_{pd} .
 - H. V_{CCI} is the V_{CC} associated with the input port.
 - I. V_{CCO} is the V_{CC} associated with the output port.

Figure 2. Load Circuit and Voltage Waveforms

PACKAGING INFORMATION

| Orderable Device | Status ⁽¹⁾ | Package Type | Package Drawing | Pins | Package Qty | Eco Plan ⁽²⁾ | Lead/Ball Finish | MSL Peak Temp ⁽³⁾ |
|------------------|-----------------------|-----------------------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| SN74AVCA406LGQSR | ACTIVE | BGA MI CROSTAR JUNIOR | GQS | 24 | 2500 | TBD | SNPB | Level-1-240C-UNLIM |
| SN74AVCA406LGXYR | ACTIVE | BGA MI CROSTAR JUNIOR | GXY | 20 | 2500 | TBD | SNPB | Level-1-240C-UNLIM |
| SN74AVCA406LZQSR | ACTIVE | BGA MI CROSTAR JUNIOR | ZQS | 24 | 2500 | Green (RoHS & no Sb/Br) | SNAGCU | Level-1-260C-UNLIM |
| SN74AVCA406LZXYR | ACTIVE | BGA MI CROSTAR JUNIOR | ZXY | 20 | 2500 | Green (RoHS & no Sb/Br) | SNAGCU | Level-1-260C-UNLIM |

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION



QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------------|----------------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74AVCA406LQSR | BGA MICROSTAR JUNIOR | GQS | 24 | 2500 | 330.0 | 12.4 | 3.3 | 3.3 | 1.6 | 8.0 | 12.0 | Q1 |
| SN74AVCA406LGXYR | BGA MICROSTAR JUNIOR | GXY | 20 | 2500 | 330.0 | 12.4 | 2.8 | 3.3 | 1.0 | 4.0 | 12.0 | Q2 |
| SN74AVCA406LZQSR | BGA MICROSTAR JUNIOR | ZQS | 24 | 2500 | 330.0 | 12.4 | 3.3 | 3.3 | 1.6 | 8.0 | 12.0 | Q1 |
| SN74AVCA406LZXYP | BGA MICROSTAR JUNIOR | ZXY | 20 | 2500 | 330.0 | 12.4 | 2.8 | 3.3 | 1.0 | 4.0 | 12.0 | Q2 |


TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|------------------|----------------------|-----------------|------|------|-------------|------------|-------------|
| SN74AVCA406LGQSR | BGA MICROSTAR JUNIOR | GQS | 24 | 2500 | 340.5 | 338.1 | 20.6 |
| SN74AVCA406LGXYR | BGA MICROSTAR JUNIOR | GXY | 20 | 2500 | 340.5 | 338.1 | 20.6 |
| SN74AVCA406LZQSR | BGA MICROSTAR JUNIOR | ZQS | 24 | 2500 | 340.5 | 338.1 | 20.6 |
| SN74AVCA406LZXYR | BGA MICROSTAR JUNIOR | ZXY | 20 | 2500 | 340.5 | 338.1 | 20.6 |

ZQS (S-PBGA-N24)


PLASTIC BALL GRID ARRAY



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Falls within JEDEC MO-225
 - D. This package is lead-free.

GQS (S-PBGA-N24)

PLASTIC BALL GRID ARRAY




4201012/D 01/02

- NOTES: A. All linear dimensions are in millimeters.
 B. This drawing is subject to change without notice.
 C. MicroStar Junior™ BGA configuration
 D. Falls within JEDEC MO-225

MicroStar Junior is a trademark of Texas Instruments.

GXY (S-PBGA-N20)


PLASTIC BALL GRID ARRAY



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.

ZXY (S-PBGA-N20)

PLASTIC BALL GRID ARRAY



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. This package is a lead-free solder ball design.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

| | |
|-----------------------------|--------------------------------------------------------------------|
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DLP® Products | www.dlp.com |
| DSP | dsp.ti.com |
| Clocks and Timers | www.ti.com/clocks |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| RFID | www.ti-rfid.com |
| RF/IF and ZigBee® Solutions | www.ti.com/lprf |

Applications

| | |
|--------------------|--------------------------------------------------------------------------|
| Audio | www.ti.com/audio |
| Automotive | www.ti.com/automotive |
| Broadband | www.ti.com/broadband |
| Digital Control | www.ti.com/digitalcontrol |
| Medical | www.ti.com/medical |
| Military | www.ti.com/military |
| Optical Networking | www.ti.com/opticalnetwork |
| Security | www.ti.com/security |
| Telephony | www.ti.com/telephony |
| Video & Imaging | www.ti.com/video |
| Wireless | www.ti.com/wireless |

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2009, Texas Instruments Incorporated