

## Multistandard Video-IF and Quasi Parallel Sound Processing

### Description

The TDA4470 is an integrated bipolar circuit for multi-standard video/sound IF (VIF/SIF) signal processing in TV/VCR and multimedia applications. The circuit processes all TV video IF signals with negative

modulation (e.g., B/G standard), positive modulation (e.g., L standard) and the AM, FM/NICAM sound IF signals.

### Features

- 5 V supply voltage; low power consumption
- Active carrier generation by FPLL principle (frequency-phase-locked-loop) for true synchronous demodulation
- Very linear video demodulation, good pulse response and excellent intermodulation figures
- VCO circuit is operating on picture carrier frequency, the VCO frequency is switchable for L'-mode
- Alignment-free AFC without external reference circuit, polarity of the AFC curve is switchable
- VIF-AGC for negative modulated signals (peak sync detection) and for positive modulation (peak white/black level detector)
- Tuner AGC with adjustable take over point
- Alignment-free quasi parallel sound (QPS) mixer for FM/NICAM sound IF signals
- Intercarrier output signal is gain controlled (necessary for digital sound processing)
- Complete alignment-free AM demodulator with gain controlled AF output
- Separate SIF-AGC with average detection
- Two independent SIF inputs
- Parallel operation of the AM demodulator and QPS mixer (for NICAM-L stereo sound)
- Package and relevant pinning is compatible with the single standard version TDA4472, simplifies the design of an universal IF module

**Package:** 28 pin shrink-dual-inline-plastic (SDIP28)  
28 pin small-outline-plastic (SO28)

### Ordering Information

Extended Type Number	Package	Remarks
TDA4470-BSD	SDIP28	
TDA4470-BFLG3	SO28	Delivery in taped for,

## Block Diagram




Figure 1. Block diagram

## Circuit Description

### Vision IF Amplifier

The video IF signal (VIF) is fed through a SAW filter to the differential input (pin 6-7) of the VIF amplifier. This amplifier consists of three AC-coupled amplifier stages. Each differential amplifier is gain controlled by the automatic gain control (VIF-AGC). Output signal of the VIF amplifier is applied to the FPLL carrier generation and the video demodulator.

### Tuner and VIF-AGC

At pin 8 the VIF-AGC charges/discharges the AGC capacitor to generate a control voltage for setting gain of VIF amplifier and tuner in order to keep the video output signal at a constant level. Therefore in case of all negative modulated signals (e.g. B/G standard) the sync level of the demodulated video signal is the criterion for a fast charge/discharge of the AGC capacitor. For positive modulation (e.g. L standard) the peak white level of video signal controls the charge current. In order to reduce reaction time for positive modulation, where a large time constant is needed, an additional black level detector controls the discharge current in the event of decreasing VIF input signal. The control voltage (AGC voltage at pin 8) is transferred to an internal control signal, and is fed to the tuner AGC to generate the tuner AGC current at pin 11 (open collector output). Take over point of the tuner AGC can be adjusted at pin 10 by a potentiometer or an external DC voltage (from interface circuit or microprocessor).

### FPLL, VCO and AFC

The FPLL circuit (frequency phase locked loop) consists of a frequency and phase detector to generate control voltage for the VCO tuning. In the locked mode the VCO is controlled by the phase detector and in unlocked mode the frequency detector is superimposed. The VCO operates with an external resonance circuit (L and C parallel) and is controlled by internal varicaps. The VCO control voltage is also converted to a current and represents the AFC output signal at pin 22. With the AFC switch (pin 19) three operating conditions of the AFC are possible: AFC curve "rising" or "falling" and AFC "off".

A practicable VCO alignment of the external coil is the adjustment to zero AFC output current at pin 22. At centre frequency the AFC output current is equal to zero. Furthermore, at pin 14, the VCO centre frequency can be switched for setting to the required 'L' value (L standard).

The optional potentiometer at pin 26 allows an offset compensation of the VCO phase for improved sound quality (fine adjustment). Without a potentiometer (open circuit at pin 26) this offset compensation is not active.

The oscillator signal passes a phase shifter and supplies the in-phase signal ( $0^\circ$ ) and the quadrature signal ( $90^\circ$ ) of the generated picture carrier.

### Video Demodulation and Amplifier

The video IF signal, which is applied from the gain controlled IF amplifier, is multiplied with the inphase component of the VCO signal. The video demodulator is designed for low distortion and large bandwidth. The demodulator output signal passes an integrated low pass filter for attenuation of the residual vision carrier and is fed to the video amplifier. The video amplifier is realized by an operational amplifier with internal feedback and 8 MHz bandwidth ( $-3$  dB). A standard depending DC level shift in this stage delivers the same sync level for positive and negative modulation. An additional noise clipping is provided. The video signal is fed to VIF-AGC and to the video output buffer. This amplifier with 6 dB gain offers easy adaptation of the sound trap. For nominal video IF modulation the video output signal at pin 12 is  $2 V_{pp}$ .

### Sound IF Amplifier and SIF-AGC

The SIF amplifier is nearly identical with the 3-stage VIF amplifier. Merely the first amplifier stage exists twice and is switchable by a control voltage at pin 3. Therefore with a minimal external expense it is possible to switch between two different SAW filters. Both SIF inputs features excellent cross-talk attenuation and an input impedance which is independent from the switching condition.

The SIF-AGC is related to the average level of AM- or FM-carrier and controls the SIF amplifier to provide a constant SIF signal to the AM demodulator and QPS mixer.

### AM Demodulator

The alignment-free AM demodulator is realized by a synchronous detector. The modulated SIF signal from the SIF amplifier output is multiplied in phase with the limited SIF signal (AM is removed). The AF signal of the demodulator output is fed to the output amplifier and to the SIF-AGC. For all TV standards with negative video modulation (e.g. B/G standard) the AF output signal (pin 25) is switched off by the standard switch.

### Quasi-Parallel-Sound (QPS) Mixer

The QPS mixer is realized by a multiplier. The SIF signal (FM or NICAM carrier) is converted to the intercarrier frequency by the regenerated picture carrier (quadrature signal) which is provided from the VCO. The intercarrier signal is fed via an output amplifier to pin 24.

## Standard Switch

To have equal polarity of the video output signal the polarity can be switched in the demodulation stage in accordance with the TV standard. Additionally a standard dependent DC level shift in the video amplifier delivers the same sync level. Parallel the correct VIF-AGC is selected for positive or negative modulated VIF signals. In case of negative modulation (e.g. B/G standard) the AM output signal is switched off. For positive modulation (L standard) the AM demodulator and QPS mixer is active. This condition allows a parallel operation of the AM sound signal and the NICAM-L stereo sound.

## L' Switch

With a control voltage at pin 14 the VCO frequency can be switched for setting to the required L' value (L' standard). Also a fine adjustment of the L'-VCO centre frequency is possible by a potentiometer. The L' switch is only active for positive modulated video IF-signals (standard switch in L mode).

## AFC Switch

The AFC output signal at pin 22 can be controlled by a switching voltage at pin 19. It is possible to select an AFC output signal with rising- or falling AFC curve and to switch off the AFC.

## VCR Mode

For the VCR mode in a TV set (external video source selected) it is recommendable to switch off the IF circuit. With an external switching voltage at pin 6 or 7 the IF amplifiers are switched off and all signal output levels at pin 12, 24, 25 are according to the internal DC voltage.

## Internal Voltage Stabilizer

The internal bandgap reference ensures constant performance independent of supply voltage and temperature.

## Pin Description




Figure 2.

Pin	Symbol	Function
1, 2	$V_{i, SIF1}$	SIF1 input (symmetrical)
3	$V_{SW}$	Input selector switch
4, 9, 16	GND	Ground
5	$C_{AGC}$	SIF-AGC (time constant)
6, 7	$V_{i, VIF}$	VIF input (symmetrical)
8	$C_{AGC}$	VIF-AGC (time constant)
10	$R_{top}$	Take over point, tuner AGC
11	$I_{tun}$	Tuner AGC output current
12	$V_{o, vid}$	Video output
13	$V_{SW}$	Standard switch
14	$V_{SW}$	L' switch
15	$C_{bl}$	Black level capacitor
17	$C_{ref}$	Internal reference voltage
18	LF	Loop filter
19	$V_{SW}$	AFC switch
20, 21	$V_{VCO}$	VCO circuit
22	$V_{AFC}$	AFC output
23	$V_S$	Supply voltage
24	$V_{O, FM}$	Intercarrier output
25	$V_{O, AM}$	AF output – AM sound
26	$R_{comp}$	Offset compensation
27, 28	$V_{i, SIF2}$	SIF 2 input (symmetrical)

## Absolute Maximum Ratings

Reference point pin 4 (9, 16), unless otherwise specified

Parameters/Conditions Pins	Symbol	Value	Unit
Supply voltage SDIP28 package SO28 package	Pin 23 $V_S$ $V_S$	9.0 6.0	V V
Supply current	Pin 23 $I_S$	75	mA
Power dissipation	SDIP28 package SO28 package $P$ $P$	675 450	mW mW
Output currents	Pins 12, 24 and 25 $I_{out}$	5	mA
External voltages	$V_{ext}$		
Pins 1, 2, 5 to 8, 10, 12, 14, 17, 18 and 24 to 28		+4.5	V
Pins 15, 20 and 21		+3.5	V
Pin 11		+13.5	V
Pins 3, 13, 19 and 22		$V_S$	V
Junction temperature	$T_j$	+125	°C
Storage temperature	$T_{stg}$	-25 to +125	°C
Electrostatic handling *) all pins	$V_{ESD}$	t.b.d.	V

\*) Equivalent to discharging a 200 pF capacitor through a 0  $\Omega$  resistor.

## Operating Range

Parameters/Conditions Pins	Symbol	Value	Unit
Supply voltage range SDIP28 package SO28 package	Pin 23 $V_S$ $V_S$	4.5 to 9.0 4.5 to 6.0	V V
Ambient temperature	$T_{amb}$	0 to +85	°C

## Thermal Resistance

Parameters	Symbol	Maximum	Unit
Junction-ambient, when soldered to PCB SDIP28 package SO28 package	$R_{thJA}$ $R_{thJA}$	55 75	K/W K/W

## Electrical Characteristics

$V_S = +5$  V,  $T_{amb} = +25$ °C; reference point pin 4 (9, 16), unless otherwise specified

Parameters	Test Conditions / Pins	Symbol	Min.	Typ.	Max.	Unit
<b>DC-supply</b>						
<b>Pin 23</b>						
Supply voltage		$V_S$	4.5	5.0	9.0	V
Supply current		$I_S$		65	75	mA
<b>VIF-input</b>						
<b>Pin 6-7</b>						
Input sensitivity (RMS value)	for FPLL locked	$v_{in}$		80	120	$\mu$ V
Input impedance	see note 1	$R_{in}$		1.2		k $\Omega$
Input capacitance	see note 1	$C_{in}$		2		pF

Parameters	Test Conditions / Pins	Symbol	Min.	Typ.	Max.	Unit
<b>VIF-AGC</b>						
<b>Pins 8 and 15</b>						
IF gain control range		$G_V$	60	65		dB
AGC capacitor	Pin 8	$C_{AGC}$		2.2		$\mu\text{F}$
Black level capacitor	Pin 15	$C_{BL}$		100		nF
Switching voltage: VCR mode	see note 2	$V_{sw}$		4.0		V
Switching current: VCR mode	see note 2	$I_{sw}$		50		$\mu\text{A}$
<b>Tuner-AGC</b>						
<b>Pins 10 and 11 see note 3</b>						
Available tuner-AGC current		$I_{tun}$	1	2	4	mA
Allowable output voltage		$V_{11}$	0.3		13.5	V
IF slip – tuner AGC	current $I_{tun}$ : 10 to 90%	$\Delta G_{IF}$		8	10	dB
IF input signal for minimum take over point	$R_{top} = 10 \text{ k}\Omega$ ( $V_{top} = 4.5 \text{ V}$ )	$v_{in}$			4	mV
IF input signal for maximum take over point	$R_{top} = 0$ , ( $V_{top} = 0.8 \text{ V}$ )	$v_{in}$	40			mV
Variation of the take over point by temperature	$\Delta T_{amb} = 55^\circ\text{C}$ VIF-AGC: $G_V = 46 \text{ dB}$	$\Delta v_{in}$		2	3	dB
<b>FPLL and VCO</b>						
<b>Pins 18, 20, 21 and 26</b>						
Max. oscillator frequency	for carrier generation	$f_{vco}$	70			MHz
Vision carrier capture range	$f_{vco} = 38.9 \text{ MHz}$ , $C_{vco} = 6.8 \text{ pF}$	$\Delta f_{cap}$	$\pm 1.5$	$\pm 2$		MHz
Oscillator drift (free running) as function of temperature	see note 4, $\Delta T_{amb} = 55^\circ\text{C}$ , $C_{vco} = 6,8 \text{ pF}$ , $f_{vco} = 38.9 \text{ MHz}$	$\Delta f/\Delta T$			-0.3	%
<b>Video output</b>						
<b>Pin 12</b>						
Output current – source – sink		$\pm I_{12}$	2		5 3	mA mA
Output resistance	see note 1	$R_{out}$			100	$\Omega$
Video output signal	peak to peak value	$v_{o,vid}$	1.8	2.0	2.2	V
Difference of the video signals	between B/G and L	$\Delta v_{o,vid}$			10	%
Sync level		$V_{sync}$		1.2		V
Zero carrier level for neg. modulation, ultra white level	$V_{13} = V_S$ $V_8 = 3 \text{ V}$	$V_{DC}$		3.4		V
Zero carrier level for pos. modulation, ultra black level	$V_{13} = 0$ $V_8 = 3 \text{ V}$	$V_{DC}$		1.15		V
Supply voltage influence on the ultra white and ultra black level		$\Delta V/V$		1		%/V
Video bandwidth (-3 dB)	$R_L \geq 1 \text{ k}\Omega$ , $C_L \leq 50 \text{ pF}$	B	6	8		MHz
Video frequency response over the AGC range		$\Delta B$			2.0	dB
Differential gain error		DG		2	5	%
Differential phase error		DP		2	5	deg

Parameters	Test Conditions / Pins	Symbol	Min.	Typ.	Max.	Unit
Intermodulation 1.07 MHz	see note 5	$\alpha_{IM}$	52	60		dB
Video signal to noise ratio	weighted, CCIR-567	S/N	56	60		dB
Residual vision carrier fundamental wave 38.9 MHz and second harmonic 77.8 MHz		$V_{res1}$		2	10	mV
Lower limiting level	below sync level	$\Delta V_{lim1}$		400		mV
Upper limiting level	above ultra white level	$\Delta V_{lim2}$		600		mV
Ripple rejection	see note 1, pin 23/pin 12	RR	35			dB
<b>Standard switch Pin 13</b>						
Control voltage for mode 1: neg. modulated video-IF signals and AM/NICAM sound	see note 6	$V_{SW}$	2.0		$V_S$	V
Control voltage for mode 2: pos. modulated video-IF signals and AM/L-NICAM sound		$V_{SW}$	0		0.8	V
Switching current		$I_{SW}$		$\pm 100$		$\mu A$
<b>AFC output Pin 22</b>						
Control slope		$\Delta I/\Delta f$		0.7		$\mu A/kHz$
Frequency drift by temperature	related to the picture carrier frequency			0.25	0.6	%
Output voltage upper limit lower limit		$V_{AFC}$	$V_S - 0.4$		0.4	V V
Output current		$I_{AFC}$		$\pm 0.2$		mA
<b>AFC switch Pin 19</b>						
Control voltage: AFC "off" AFC curve rising AFC curve falling	see note 7	$V_{SW}$	0 1.5 3.5		0.8 2.5 $V_S$	V V V
Switching current		$I_{SW}$		$\pm 100$		$\mu A$
<b>L' switch Pin 14</b>						
Control voltage: L' frequency + L'-VCO alignment L standard	see note 8	$V_{SW}$	0 3.4		3.0 $V_S$	V V
Switching current	$V_{SW} = 0$	$I_{SW}$		700		$\mu A$
<b>SIF inputs Pin 1-2, 27-28</b>						
Input sensitivity (RMS value)	output signal at pin 24/25: -3 dB	$v_{in}$		80	120	$\mu V$
Input impedance	see note 1	$R_{in}$		1.2		k $\Omega$
Input capacitance	see note 1	$C_{in}$		2		pF
<b>SIF-AGC Pin 5</b>						
IF gain control range		$G_V$	60	65		dB
AGC capacitor		$C_{AGC}$		10		$\mu F$

Parameters	Test Conditions / Pins	Symbol	Min.	Typ.	Max.	Unit
<b>Intercarrier output-FM</b>						
<b>Pin 24</b>		<b>see note 9</b>				
DC output voltage		$V_{DC}$		2		V
Output resistance	see note 1	$R_{out}$		150		$\Omega$
Sound IF output voltage (5.5 MHz output voltage)	$v_{in} = 10 \text{ mV}$	$v_{out}$		300		mV
Weighted signal to noise ratio: (CCIR 468)	Ref. signal: $v_{in} = 10 \text{ mV}$ ; FM dev. = $\pm 27 \text{ kHz}$ $f_{mod} = 1 \text{ kHz}$ ; tested with the double FM demod. U2860B; B/G modulated VIF signal					
		Black screen: Channel 1/2	S/N	60/58		dB
		Grid pattern: Channel 1/2	S/N	54/52		dB
		Grey screen 50%: Channel 1/2	S/N	60/57		dB
Ripple rejection	see note 1, pin 23/pin24	RR	35			dB
<b>AF output-AM</b>						
<b>Pin 25</b>		<b>see note 10</b>				
DC output voltage		$V_{DC}$		2.2		V
Output resistance	see note 1	$R_{out}$		150		$\Omega$
AF output voltage		$v_{oAF}$		500		mV
Total harmonic distortion	$m = 54\%$ $f_{mod} = 1 \text{ kHz}$ and $12.5 \text{ kHz}$	THD		1	2	%
Signal to noise ratio	Reference: $m = 54\%$ , $f_{mod} = 1 \text{ kHz}$ , 22 kHz low pass filter	S/N		65		dB
Ripple rejection	see note 1, pin 23/pin25	RR	28			dB
<b>SIF input selector switch</b>						
<b>Pin 3</b>						
Control voltage: input 1 active input 2 active	see note 11	$V_{SW}$	2.0 0		$V_S$ 0.8	V V
Switching current		$I_{SW}$		$\pm 100$		$\mu\text{A}$

## Notes

- This parameter is given as an application information and not tested during production.
- In VCR mode the VIF- and SIF path is switched off.
- Adjustment of turn over point (delayed tuner AGC) with external resistor  $R_{top}$  or external voltage  $V_{top}$  possible.
- The oscillator drift is related to the picture carrier frequency, at external temperature-compensated LC circuit.
- $\alpha (1.07) = 20 \log (4.43 \text{ MHz component}/1.07 \text{ MHz component})$ ;  $\alpha (1.07)$  value related to black-white signal input signal conditions: picture carrier = 0 dB, colour carrier = -6 dB, sound carrier = -24 dB
- Without external control at pin 13 the IC automatically operates in mode 1:  
⇒ negative modulated video-IF signals and FM/NICAM sound signals.
- Without control voltage at pin 19 falling AFC curve is automatically selected.
- With open circuit at pin 14 the L' switch is not active.
- Picture carrier PC = 38.9 MHz; sound carrier  $SC_1 = 33.4 \text{ MHz}$ ,  $SC_2 = 33.16 \text{ MHz}$ ;  
PC/ $SC_1$  = 13 dB; PC/ $SC_2$  = 20 dB; PC unmodulated (equivalent to sync peak level).
- Sound carrier SC = 32.4 MHz, modulated with  $f_{mod} = 1 \text{ kHz}$ ,  $m = 54\%$ ;  $v_{in} = 10 \text{ mV}$
- Without control voltage at pin 3 SIF input 1 is automatically selected.

## TDA4470-B




Figure 3. Test circuit



## Internal Pin Configuration




Figure 5. Sound IF inputs (pin 1-2, 27-28)




Figure 8. Video IF input (pin 6-7)




Figure 6. Input selector switch (pin 3)




Figure 9. VIF-AGC time constant (pin 8)




Figure 7. SIF-AGC time constant (pin 5)




Figure 10. Tuner AGC - take over point (pin 10)




Figure 11. Tuner AGC – output (pin 11)




Figure 14. Black level capacitor (pin 15)




Figure 12. Video output (pin 12)




Figure 15. Internal reference voltage (pin 17)




Figure 13. Standard switch (pin 13)




Figure 16. Loop filter (pin 18)




Figure 17. AFC switch (pin 19)




Figure 20. Intercarrier output (pin 24)




Figure 18. VCO (pin 20-21)




Figure 21. AF output AM sound (pin 25)




Figure 19. AFC output (pin 22)





Figure 22. VCO offset compensation (pin 26)

## Dimensions in mm

Package: 28 pin shrink-dual-in line-plastic (SDIP28)



95 10610

## Ozone Depleting Substances Policy Statement

It is the policy of **TEMIC TELEFUNKEN microelectronic GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

**TEMIC TELEFUNKEN microelectronic GmbH** semiconductor division has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

**TEMIC** can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use TEMIC products for any unintended or unauthorized application, the buyer shall indemnify TEMIC against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

TEMIC TELEFUNKEN microelectronic GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423

## Internal Pin Configuration

Figure 23. Sound IF inputs (pin 1-2, 27-28)

Figure 24. Input selector switch (pin 3)

Figure 25. SIF-AGC time constant (pin 5)

Figure 26. Video IF input (pin 6-7)

Figure 27. VIF-AGC time constant (pin 8)

Figure 28. Tuner AGC – take over point (pin 10)

Figure 29. Tuner AGC – output (pin 11)

Figure 30. Video output (pin 12)

Figure 31. Standard switch (pin 13)

Figure 32. L' switch (pin 14)

Figure 33. Black level capacitor (pin 15)

Figure 34. Internal reference voltage (pin 17)

Figure 35. Loop filter (pin 18)

Figure 36. AFC switch (pin 19)

Figure 37. VCO (pin 20-21)

Figure 38. AFC output (pin 22)

Figure 39. Intercarrier output (pin 24)

Figure 40. AF – AM output (pin 25)

Figure 41. VCO offset compensation (pin 26)


# TDA4470-B

# TEMIC


TELEFUNKEN Semiconductors

## Dimensions in mm

Package: SDIP28



Package: SO28



## Ozone Depleting Substances Policy Statement

It is the policy of **TEMIC TELEFUNKEN microelectronic GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

**TEMIC TELEFUNKEN microelectronic GmbH** semiconductor division has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

**TEMIC** can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use TEMIC products for any unintended or unauthorized application, the buyer shall indemnify TEMIC against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

TEMIC TELEFUNKEN microelectronic GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423