

## CMOS 4-Bit Microcontroller

# TMP47P403VN TMP47P403VM



The TMP47P403V is the system evaluation LSI of TMP47C103/203 with a 32-Kbit one-time PROM. The TMP47P403V programs / verifies using an adapter socket to connect with PROM programmer, as it is in TMM27256AD.

In addition, the TMP47P403V and the TMP47C103/203 are pin compatible. The TMP47P403V operates as the same as the TMP47C103/203 by programming to the internal PROM.

| Part No.    | ROM          | RAM         | Package           | Adaptor Socket |
|-------------|--------------|-------------|-------------------|----------------|
| TMP47P403VN | OTP          | 128 × 4-bit | P-SDIP28-400-1.78 | BM1140         |
| TMP47P403VM | 4096 × 8-bit |             | P-SOP28-450-1.27  | BM1141         |

## Pin Assignment (Top View)

P-SDIP28-400-1.78 / P-SOP28-450-1.27



000707EBA1

- For a discussion of how the reliability of microcontrollers can be predicted, please refer to Section 1.3 of the chapter entitled Quality and Reliability Assurance / Handling Precautions.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

**Pin Function**

The TMP47P403V has MCU mode and PROM mode.

## (1) MCU mode

The TMP47C103/203 and the TMP47P403V are pin compatible.

## (2) PROM mode

| Pin Name                  | Input / Output | Functions                                      | Pin Name (MCU mode)      |
|---------------------------|----------------|--|--------------------------|
| A11 to A8                 | Input          | Address inputs                                 | R63 to R60               |
| A7 to A4                  |                |  | R53 to R50               |
| A3 to A0                  |                |  | R43 to R40               |
| I7 to I5                  | I/O            | Data inputs / outputs                          | R72 to R70               |
| I4                        |                |  | R90                      |
| I3 to I0                  |                |  | R83 to R80               |
| $\overline{\text{CE}}$    | Input          | Chip Enable input                              | R92                      |
| $\overline{\text{OE}}$    |                | Output Enable input                            | R91                      |
| VPP                       | Power supply   | + 12.5 V / 5 V (Program supply voltage)        | $\overline{\text{HOLD}}$ |
| VCC                       |                | + 5 V  | VDD                      |
| VSS                       |                | 0 V  | VSS                      |
| $\overline{\text{RESET}}$ | Input          | PROM mode setting pin. Be fixed to low level.  |                          |
| XIN                       | Input          | Input the clock from the external oscillator.  |                          |
| XOUT                      | Input          | Be pulled up to VCC level. (750 $\Omega$ typ.) |                          |

## Operational Description

The following is an explanation of hardware configuration and operation in relation to the TMP47P403V. The TMP47P403V is the same as the TMP47C103/203 except that an OTP is used instead of a built-in mask ROM.

### 1. Operation mode

The TMP47P403V has an MCU mode and a PROM mode.

#### 1.1 MCU mode

The MCU mode is set by attaching a resonator between the XIN and Xout pins. Operation in the MCU mode is the same as for the TMP47C103/203. In the TMP47P403V, RC oscillation is impossible.

##### 1.1.1 Program Memory

The program storage area are as shown in Figure 1-1. Data conversion tables must be set in two locations when using the TMP47P403V to check TMP47C103/203 operation.




Figure 1-1. Program area

## Electrical Characteristics

## Absolute Maximum Ratings

(V<sub>SS</sub> = 0 V)

| Parameter                                   | Symbol             | Pins             | Ratings                        | Unit |
|---|--------------------|------------------|--------------------------------|------|
| Supply Voltage                              | V <sub>DD</sub>    |                  | – 0.3 to 6.5                   | V    |
| Program Voltage                             | V <sub>PP</sub>    | HOLD / VPP pin   | – 0.3 to 13.0                  | V    |
| Input Voltage                               | V <sub>IN</sub>    |                  | – 0.3 to V <sub>DD</sub> + 0.3 | V    |
| Output Voltage                              | V <sub>OUT</sub>   |                  | – 0.3 to V <sub>DD</sub> + 0.3 | V    |
| Output Current (Per 1 pin)                  | I <sub>OUT1</sub>  | Port R5, R6      | 30                             | mA   |
|   | I <sub>OUT2</sub>  | Port R4          | 15                             |      |
|   | I <sub>OUT3</sub>  | Ports R7, R8, R9 | 3.2                            |      |
| Output Current (Total)                      | Σ I <sub>OUT</sub> | Port R4, R5, R6  | 120                            | mA   |
| Power Dissipation [T <sub>opr</sub> = 70°C] | PD                 | DIP              | 300                            | mW   |
|   |                    | SOP              | 180                            |      |
| Soldering Temperature (time)                | T <sub>sld</sub>   |                  | 260 (10 s)                     | °C   |
| Storage Temperature                         | T <sub>stg</sub>   |                  | – 55 to 125                    | °C   |
| Operating Temperature                       | T <sub>opr</sub>   |                  | – 30 to 70                     | °C   |

**Note:** The absolute maximum ratings are rated values which must not be exceeded during operation, even for an instant. Any one of the ratings must not be exceeded. If any absolute maximum rating is exceeded, a device may break down or its performance may be degraded, causing it to catch fire or explode resulting in injury to the user. Thus, when designing products which include this device, ensure that no absolute maximum rating value will ever be exceeded.

## Recommended Operating Conditions

(V<sub>SS</sub> = 0 V, T<sub>opr</sub> = – 30 to 70°C)

| Parameter          | Symbol           | Pins                    | Conditions                     | Min                    | Max                    | Unit |
|--------------------|------------------|-------------------------|--------------------------------|------------------------|------------------------|------|
| Supply Voltage     | V <sub>DD</sub>  |                         | f <sub>c</sub> = 6.0 MHz       | 4.5                    | 5.5                    | V    |
|                    |                  |                         | f <sub>c</sub> = 4.2 MHz       | 2.7                    |                        |      |
|                    |                  |                         | HOLD mode                      | 2.0                    |                        |      |
| Input High Voltage | V <sub>IH1</sub> | Except Hysteresis Input | In the normal operating area   | V <sub>DD</sub> × 0.7  | V <sub>DD</sub>        | V    |
|                    | V <sub>IH2</sub> | Hysteresis Input        |                                | V <sub>DD</sub> × 0.75 |                        |      |
|                    | V <sub>IH3</sub> |                         | In the HOLD mode               | V <sub>DD</sub> × 0.9  |                        |      |
| Input Low Voltage  | V <sub>IL1</sub> | Except Hysteresis Input | In the normal operating area   | 0                      | V <sub>DD</sub> × 0.3  | V    |
|                    | V <sub>IL2</sub> | Hysteresis Input        |                                |                        | V <sub>DD</sub> × 0.25 |      |
|                    | V <sub>IL3</sub> |                         | In the HOLD mode               |                        | V <sub>DD</sub> × 0.1  |      |
| Clock Frequency    | f <sub>c</sub>   | XIN, XOUT               | V <sub>DD</sub> = 4.5 to 5.5 V | 0.4                    | 6.0                    | MHz  |
|                    |                  |                         | V <sub>DD</sub> = 2.7 to 5.5 V |                        | 4.2                    |      |

**Note:** The recommended operating conditions for a device are operating conditions under which it can be guaranteed that the device will operate as specified. If the device is used under operating conditions other than the recommended operating conditions (supply voltage, operating temperature range, specified AC/DC values etc.), malfunction may occur. Thus, when designing products which include this device, ensure that the recommended operating conditions for the device are always adhered to.

## DC Characteristics

(V<sub>SS</sub> = 0 V, T<sub>opr</sub> = – 30 to 70°C)

| Parameter   | Symbol           | Pins                    | Conditions   | Min | Typ. | Max | Unit |
|---|------------------|-------------------------|--|-----|------|-----|------|
| Hysteresis Voltage                                  | V <sub>HS</sub>  | Hysteresis Input        |  | –   | 0.7  | –   | V    |
| Input Current                                       | I <sub>IN1</sub> | RESET, HOLD             | V <sub>DD</sub> = 5.5 V, V <sub>IN</sub> = 5.5 V / 0 V | –   | –    | ± 2 | μA   |
|   | I <sub>IN2</sub> | Open drain output ports |  |     |      |     |      |
| Input Resistance                                    | R <sub>IN</sub>  | RESET                   |  | 100 | 220  | 450 | kΩ   |
| Input Low Current                                   | I <sub>IL</sub>  | Push-pull output ports  | V <sub>DD</sub> = 5.5 V, V <sub>IN</sub> = 0.4 V       | –   | –    | – 2 | mA   |
| Output Leakage Current                              | I <sub>LO</sub>  | Open drain output ports | V <sub>DD</sub> = 5.5 V, V <sub>OUT</sub> = 5.5 V      | –   | –    | 2   | μA   |
| Output Low Voltage                                  | V <sub>OL</sub>  | Port R7, R8, R9         | V <sub>DD</sub> = 4.5 V, I <sub>OL</sub> = 1.6 mA      | –   | –    | 0.4 | V    |
| Output Low Current                                  | I <sub>OL1</sub> | Port R5, R6             | V <sub>DD</sub> = 4.5 V, V <sub>OL</sub> = 1.0 V       | –   | 20   | –   | mA   |
|   | I <sub>OL2</sub> | Port R4                 |  | –   | 7    | –   |      |
| Supply Current<br>(in the Normal<br>operating mode) | I <sub>DD</sub>  |                         | V <sub>DD</sub> = 5.5 V, f <sub>c</sub> = 4 MHz        | –   | 2    | 4   | mA   |
|   |                  |                         | V <sub>DD</sub> = 3.0 V, f <sub>c</sub> = 4 MHz        | –   | 1    | 2   |      |
|   |                  |                         | V <sub>DD</sub> = 3.0 V, f <sub>c</sub> = 400 kHz      | –   | 0.5  | 1   |      |
| Supply Current<br>(in the HOLD<br>operating mode)   | I <sub>DDH</sub> |                         | V <sub>DD</sub> = 5.5 V                                | –   | 0.5  | 10  | μA   |

Note 1: Typ. values show those at T<sub>opr</sub> = 25°C, V<sub>DD</sub> = 5 V.


Note 2: Input Current I<sub>IN1</sub>: The current through resistor is not included.

Note 3: Supply Current: V<sub>IN</sub> = 5.3 V / 0.2 V (V<sub>DD</sub> = 5.5 V), 2.8 V / 0.2 V (V<sub>DD</sub> = 3.0 V)


## AC Characteristics

(V<sub>SS</sub> = 0 V, T<sub>opr</sub> = – 30 to 70°C)

| Parameter                    | Symbol           | Conditions                     | Min                       | Typ. | Max | Unit |
|------------------------------|------------------|--------------------------------|---------------------------|------|-----|------|
| Instruction Cycle Time       | t <sub>cy</sub>  | V <sub>DD</sub> = 4.5 to 5.5 V | 1.3                       | –    | 20  | μs   |
|                              |                  | V <sub>DD</sub> = 2.7 to 5.5 V | 1.9                       |      |     |      |
| High level Clock pulse Width | t <sub>WCH</sub> | For external clock operation   | 80                        | –    | –   | ns   |
| Low level Clock pulse Width  | t <sub>WCL</sub> |                                |                           |      |     |      |
| Shift data Hold Time         | t <sub>SDH</sub> |                                | 0.5 t <sub>cy</sub> – 0.3 | –    | –   | μs   |

**Note: Shift data Hold Time:**External circuit for pins  $\overline{\text{SCK}}$  and SO

Serial port (completed of transmission)



## Recommended Oscillating Conditions

(V<sub>SS</sub> = 0 V, V<sub>DD</sub> = 4.5 to 5.5 V, T<sub>opr</sub> = – 30 to 70°C)


Recommended oscillating conditions of the TMP47P403V are equal to the TMP47C103/203's but RC oscillation is impossible.

## DC/AC Characteristics

(V<sub>SS</sub> = 0 V)

## (1) Read Operation

| Parameter                 | Symbol           | Condition                      | Min                   | Typ. | Max                   | Unit |
|---------------------------|------------------|--------------------------------|-----------------------|------|-----------------------|------|
| Output Level High Voltage | V <sub>IH4</sub> |                                | V <sub>CC</sub> × 0.7 | –    | V <sub>CC</sub>       | V    |
| Output Level Low Voltage  | V <sub>IL4</sub> |                                | 0                     | –    | V <sub>CC</sub> × 0.3 | V    |
| Supply Voltage            | V <sub>CC</sub>  |                                | 4.75                  | –    | 6.0                   | V    |
| Programming Voltage       | V <sub>PP</sub>  |                                |                       |      |                       |      |
| Address Access Time       | t <sub>ACC</sub> | V <sub>CC</sub> = 5.0 ± 0.25 V | 0                     | –    | 350                   | ns   |



## (2) High Speed Programming Operation

| Parameter                     | Symbol    | Condition                 | Min                 | Typ.  | Max                 | Unit |
|-------------------------------|-----------|---------------------------|---------------------|-------|---------------------|------|
| Input High Voltage            | $V_{IH4}$ |                           | $V_{CC} \times 0.7$ | –     | $V_{CC}$            | V    |
| Input Low Voltage             | $V_{IL4}$ |                           | 0                   | –     | $V_{CC} \times 0.3$ | V    |
| Supply Voltage                | $V_{CC}$  |                           | 4.75                | –     | 6.0                 | V    |
| $V_{PP}$ Power Supply Voltage | $V_{PP}$  |                           | 12.00               | 12.50 | 13.00               | V    |
| Programming Pulse Width       | $t_{PW}$  | $V_{CC} = 6.0 \pm 0.25$ V | 0.95                | 1.0   | 1.05                | ms   |

