


CMOS 8-Bit Microcontroller
TMP88CS48AN, TMP88CS48AF

TMP88CS48A is high-speed and high-function 8-bit single-chip microcomputers whose built-in features include large-capacity RAM, multi-function timer/counter, and 10-bit AD converter, serial interface (UART/I²C bus). They are equipped with 3 phase brushless DC sensorless/sensor motor control, and AC motor inverter control.

Part No.	ROM	RAM	Package	OTP MCU
TMP88CS48AN	64 Kbytes	2 Kbytes	P-SDIP64-750-1.78	TMP88PS49N
TMP88CS48AF			P-QFP64-1420A-1.00A	TMP88PS49F

Features

- ◆ 8-bit single-chip microcomputer TLCS-870/X series microcomputer
- ◆ Interrupt sources: 25 (6 external, 19 Internal)
- ◆ I/O ports: 56 pins
 - Large-current output: 8 pins (typ. 20 mA), LED direct drive
- ◆ 16-bit timer/counter: 2 channels
 - Timer, event counter, programmable pulse generator (PPG) output, pulse width measurement, external trigger timer, window mode
- ◆ 8-bit Timer/Counter: 3 channels
 - Timer, event counter, capture (pulse width/duty measurement), pulse width modulation (PWM) output, programmable divider output (PDO) mode
- ◆ Time base timer (interrupt frequency: 1 to 16384 Hz)
- ◆ Watchdog timer
- ◆ Divider output function (frequency: 1 to 8 kHz)
- ◆ Programmable motor driver (PMD): 1 channel
 - Rotor position: minimum resolution of 250 ns for detecting rotor position
 - Motor control timer, timer capture function
 - Overload protection function
 - DC overload protection function
 - AC overload protection function (Can halt counter in 3-phase PWM output circuit)
 - Protection circuit for malfunction (urgent halt)
 - Automatic direction change, automatic position detection start
- ◆ High-speed PWM output: 2 channel
 - Cycle: 32 kHz, 64 kHz, 128 kHz (at 8 MHz operation)
 - Resolution: 8-bit, 7-bit, 6-bit mode selectable



980910EBP1

- For a discussion of how the reliability of microcontrollers can be predicted, please refer to Section 1.3 of the chapter entitled Quality and Reliability Assurance/Handling Precautions.
- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.




Purchase of TOSHIBA I²C components conveys a license under the Philips I²C Patent Rights to use these components in an I²C system, provided that the system conforms to the I²C Standard Specification as defined by Philips.


- ◆ Serial interface
 - 8-bit SIO/I²C bus
 - Universal asynchronous receiver transmitter (UART)
- ◆ 10-bit successive approximation type AD converter
 - Analog input: 16 channels
 - Conversion time: 46 μ s (at 16 MHz operation)
- ◆ Low power dissipation operation (2 modes)
 - STOP mode: Stops oscillation (battery or capacitor backup). Port output hold or high impedance selectable
 - IDLE mode: Stops CPU but continues operation of peripheral hardware. Released by interrupt (restarts CPU)
- ◆ Operating voltage: 4.5 to 5.5 V at 16 MHz operation
- ◆ Emulation pod: BM88CM49N0A

Pin Assignments


P-SDIP64-750-1.78



P-QFP64-1420-1.00A



Block Diagram



Pin Function

Pin Name	I/O	Function	
P07 (CL1/PDW1)	I/O (Input)	8-bit programmable I/O port (tri state) Input or output specifiable in units of bits. When using pins for motor control circuit, set accordingly using P0CR, then MDCR to 1.	Overload protection input 1/motor control circuit W1-phase position detection input Motor control circuit malfunction detection input 1
P06 (EMG1)			Motor control circuit U1-/V1-/W1-phase output
P05 (U1)			
P04 (V1)			
P03 (W1)			
P02 (X1)			
P01 (Y1)			
P00 (Z1)			
P17 (PDU1)	I/O (Input)	8-bit programmable I/O port (tri state) Input or output specifiable units of bits. When using pins for motor control circuit, timer/counter input, or external interrupt input, set them to input mode.	Motor control circuit U1-phase position detection input Motor control circuit V1-phase position detection input
P16 (PDV1)			
P15 (DVO/TC2)	I/O (Output/Input)		Divider output or Timer/Counter 2 input
P14 (PPG)			Programmable pulse generator output
P13 (PWM5/PDO5)	I/O (Output)	When using pins for PPG output, divider output, or PWM output/PDO output, set them to output mode.	8-BIT PWM output 5 or 8-BIT programmable divider output 5
P12 (INT2/TC1)	I/O (Input)		External interrupt input 2 or Timer/Counter 1 input
P11 (INT1)			External interrupt input 1
P10 (INT0)			External interrupt input 0
P22	I/O	3-bit I/O port	—
P21		When using pins for input port, external interrupt input, or STOP mode release input, set output latches to 1.	—
P20 (INT5/STOP)	I/O (Input)		External interrupt input 5 or STOP mode release signal input
P37			
P36			
P35			
P34			
P33			
P32			
P31			
P30			
P47 (SDA/SO)	I/O (I/O/Output)	8-bit I/O port	
P46 (SCL/SI)	I/O (I/O/Input)	When using pins for motor control circuit input, UART/I ² C/SIO, set output latches to 1.	I ² C/SIO I/O
P45 (SCK)	I/O (I/O)		
P44 (TxD)	I/O (Input)		UART data input
P43 (RxD)	I/O (Output)		UART data output
P42	I/O		—
P41			—
P40			—
P54 (HPWM1)			high-speed PWM output
P53 (HPWM0)			8-BIT PWM output 4 or,
P52 (PWM4/PDO4)	I/O (Output)	When using pins for input port, HPWM output, PWM output/PDO output, external interrupt input, or timer/counter input, set output latches to 1.	8-bit programmable divider output 4
P51 (INT4/TC4)	I/O (Input)		External interrupt 4 input or timer / counter 4 input
P50 (INT3/TC3)			External interrupt 3 input or timer / counter 3 input

Pin Name	Input/Output	Function	
P67 (AIN07) to P60 (AIN00)	I/O (Input)	8-bit programmable I/O port (tri state) Input or output specifiable in units of bits. When using pins for analog input, set to input mode using P6CR and ADCCR.	AD converter analog input
P77 (AIN17) to P70 (AIN10)	I/O (Input)	8-bit programmable I/O port (tri state) Input or output specifiable in units of bits. When using pins for analog input, set to input mode using P7CR and ADCCR.	AD converter analog input
XIN, XOUT	Input, Output	High-frequency oscillator connecting pins. For external clock input, input to XIN and leave XOUT open.	
RESET	I/O	Reset signal input, watchdog timer output, address trap reset output, system clock reset output	
TEST	Input	Shipment test pin, fix to "L" level.	
VDD, VSS	Power Supply	+ 5 V, 0 V (GND)	
VAREF, VASS		Analog reference voltage for AD conversion. Reference GND.	

Operation

1. CPU Core Functions

The CPU core consists of the CPU, system clock control circuit, and interrupt control circuit. This chapter describes the CPU core, program memory, data memory and the reset circuit.

1.1 Memory Address Map

The TMP88CS48A memory consists of four blocks: ROM, RAM, special function registers (SFR) and Data buffer registers (DBR). They are all mapped to a 1 Mbyte address space. Figure 1-1 shows the TMP88CS48A memory address map. There are 16 general-purpose registers mapped to the RAM address space.




Figure 1-1. Memory Address Maps

Electrical Characteristics

Absolute Maximum Ratings		(V _{SS} = 0 V)		
Parameter	Symbol	Pins	Ratings	Unit
Supply Voltage	V _{DD}		– 0.3 to 6.5	V
Input Voltage	V _{IN}		– 0.3 to V _{DD} + 0.3	V
Output Voltage	V _{OUT1}	Port P21, P22, RESET, Tri-state port	– 0.3 to V _{DD} + 0.3	V
	V _{OUT2}	Port P20, Sink open drain port	– 0.3 to 5.5	V
Output Current	I _{OUT1}	Ports P1, P2, P4, P5, P6, P7	3.2	mA
	I _{OUT2}	Port P0	20	
	I _{OUT3}	Port P3	30	
Output Current	ΣI _{OUT1}	Ports P1, P2, P4, P5, P6, P7	120	mA
	ΣI _{OUT2}	Port P0	60	
	ΣI _{OUT3}	Port P3	120	
Power Dissipation [Topr = 70°C]	PD	TMP88CS48AN TMP88CS48AF	600 350	mW
Soldering Temperature (time)	T _{sld}		260 (10 s)	°C
Storage Temperature	T _{stg}		– 55 to 125	°C
Operating Temperature	Topr		– 40 to 85	°C

Note: The absolute maximum ratings are rated values which must not be exceeded during operation, even for an instant. Any one of the ratings must not be exceeded. If any absolute maximum rating is exceeded, a device may break down or its performance may be degraded, causing it to catch fire or explode resulting in injury to the user. Thus, when designing products which include this device, ensure that no absolute maximum rating value will ever be exceeded.

Recommended Operating Conditions

(V_{SS} = 0 V, Topr = – 40 to 85°C)

Parameter	Symbol	Pins	Conditions	Min	Max	Unit	
Supply Voltage	V _{DD}		fc = 16 MHz	NORMAL mode IDLE mode STOP mode	4.5	5.5	V
Input High Voltage	V _{IH1}	Except hysteresis input	V _{DD} ≥ 4.5 V	V _{DD} × 0.70	V _{DD}	V	
	V _{IH2}	Hysteresis input		V _{DD} × 0.75			
	V _{IH3}		V _{DD} < 4.5 V	V _{DD} × 0.90			
Input Low Voltage	V _{IL1}	Except hysteresis input	V _{DD} ≥ 4.5 V	V _{DD} × 0.30	0	V	
	V _{IL2}	Hysteresis input		V _{DD} × 0.25			
	V _{IL3}		V _{DD} < 4.5 V	V _{DD} × 0.10			
Clock Frequency	fc	XIN, XOUT	V _{DD} = 4.5 to 5.5 V	8.0	16.0	MHz	

Note 1: The recommended operating conditions for a device are operating conditions under which it can be guaranteed that the device will operate as specified. If the device is used under operating conditions other than the recommended operating conditions (supply voltage, operating temperature range, specified AC/DC values etc.), malfunction may occur. Thus, when designing products which include this device, ensure that the recommended operating conditions for the device are always adhered to.

Note 2: Clock frequency fc: The condition of supply voltage range is the value in NORMAL and IDLE modes.

DC Characteristics			(V _{SS} = 0 V, Topr = -40 to 85°C)						
Parameter	Symbol	Pins	Conditions		Min	Typ.	Max	Unit	
Hysteresis Voltage	V _{HS}	Hysteresis inputs			-	0.9	-	V	
Input Current	I _{IN1}	TEST	V _{DD} = 5.5 V V _{IN} = 5.5 V/0 V	-	-	± 2	μA		
	I _{IN2}	Sink open drain, Tri-state ports							
	I _{IN3}	RESET, STOP							
Input Resistor (*)	R _{IN}	TEST with pull-down			20	70	170	kΩ	
		RESET			90	220	510		
Output Leakage Current	I _{OL}	Sink open drain, Tri-state ports	V _{DD} = 5.5 V, V _{OUT} = 5.5 V/0 V	-	-	± 2	μA		
Output High Voltage	V _{OH}	Tri-state ports	V _{DD} = 4.5 V, I _{OH} = -0.7 mA	4.1	-	-	V		
Output Low Current	I _{OL1}	Except XOUT, Ports P0, P3.	V _{DD} = 4.5 V, V _{OL} = 0.4 V	-	1.6	-	mA		
	I _{OL2}	Port P0	V _{DD} = 4.5 V, V _{OL} = 1.0 V	6	10	-			
	I _{OL3}	Port P3		12	20	-			
Supply Current in NORMAL Mode			V _{DD} = 5.5 V	-	32	40	mA		
Supply Current in IDLE Mode			V _{IN} = 5.3 V/0.2 V fc = 16.0 MHz	-	24	30	mA		
Supply Current in STOP Mode			V _{DD} = 5.5 V V _{IN} = 5.3 V/0.2 V	-	0.5	20	μA		

Note 1: Typical values show those at Topr = 25°C, V_{DD} = 5 V.

Note 2: Input Current I_{IN1}, I_{IN3}: The current through register is not included, when the input resistor (pull-up or pull-down) is contained.

Note 3: IDD except I_{REF}.

AD Conversion Characteristics			(Topr = -40 to 85°C)				
Parameter	Symbol	Conditions	Min	Typ.	Max		Unit
					ADCDR1	ADCDR2	
					ACK = 1		
Analog Reference Voltage	V _{AREF}	V _{AREF} - V _{ASS} ≥ 3.5 V	V _{DD} - 1.0	—	V _{DD}		V
	V _{ASS}		V _{SS}	—	1.0		
Analog Input Voltage	V _{A1N}		V _{ASS}	—	V _{AREF}		V
Analog Supply Current	I _{REF}	V _{AREF} = 5.5 V, V _{ASS} = 0.0 V	—	0.5	1.0		mA
Non-Linearity Error		V _{DD} = 5.0 V, V _{SS} = 0.0 V V _{AREF} = 5.000 V V _{ASS} = 0.000 V	—	—	± 1	± 2	LSB
Zero Point Error			—	—	± 1	± 2	
Full Scale Error			—	—	± 1	± 2	
Total Error			—	—	± 2	± 4	

Note 1: ADCCR1: 8-bit AD conversion result (1LSB = ΔV_{AREF}/256)
ADCCR2: 10-bit AD conversion result (1LSB = ΔV_{AREF}/1024)

Note 2: Total error includes all errors except quantization error.

AC Characteristics


(V_{SS} = 0 V, V_{DD} = 4.5 to 5.5 V, Topr = -40 to 85°C)

Parameter	Symbol	Conditions	Min	Typ.	Max	Unit
Machine Cycle Time	tcy	NORMAL mode	0.25	-	0.5	μs
		IDLE mode				
High Level Clock Pulse Width	twCH	For external clock operation (XIN input)	31.25	-	62.5	ns
Low Level Clock Pulse Width	twCL					

Recommended Oscillating Conditions

(V_{SS} = 0 V, V_{DD} = 4.5 to 5.5 V, Topr = -40 to 85°C)

Parameter	Oscillator	Oscillation Frequency	Recommended Oscillator	Recommended Constant	
				C ₁	C ₂
High-frequency Oscillation	Ceramic Resonator	16 MHz	MURATA CSA16.00MXZ	5 pF	5 pF
			MURATA CST16.00MXW	built-in 5 pF	built-in 5 pF



Note: An electrical shield by metal shield on the surface of IC package should be recommendable in order to prevent the device from the high electric field stress applied from CRT (Cathode Ray Tube) for continuous reliable operation.