

Podwójna tetroda mocy

UEL 11


Audion, wzm. m.cz., wzm. oporowy

Stalowy



$$U_z = 48 \text{ V}$$

$$I_z = 100 \text{ mA}$$



Wartości charakterystyczne i robocze

U_a	100	100	200	V
U_{s2}	30	100	200	V
U_{s1}	0	—3	—6	V
R_k	250	250	250	Ω
I_a	0,8	10	22	mA
I_{s2}	0,43	2	6	mA
S_a	1,6	4,5	5,2	mA/V
Q_a	280	2,5	30	k Ω
R_a	200	9	9	k Ω
R_{s2+s4}	300+1000	—	—	k Ω
r_{s2}	20	—	—	k Ω
h	—	10	10	%
U_{wej}	—	2,2	4,5	V
P_{wyj}	—	—	2	W

Wartości graniczne

$U_{a\max}$	250	250	V
$U_{s2\max}$	100	250	V
$P_{a\max}$	1	5	W
$P_{s2\max}$	0,2	0,8	W
$I_{k\max}$	30	30	mA
$U_{w/k\max}$	—	150	V
$R_{s1\max}$	2	1,2	M Ω

Pojemności

C_{wej}	5,4	pF
C_{wyj}	5,8	pF
$C_{s1/a}$	<0,14	pF
$C_{s1I/aII}$	<0,008	pF
$C_{s1/w}$	<0,005	pF

TYPY PODOBNE

VEL 11

