

**N - CHANNEL ENHANCEMENT MODE
 POWER MOS TRANSISTORS**


TYPE	V _{DSS}	R _{DS(on)}	I _D [■]
IRF740	400 V	0.55 Ω	10 A
IRF740FI	400 V	0.55 Ω	5.5 A
IRF741	350 V	0.55 Ω	10 A
IRF741FI	350 V	0.55 Ω	5.5 A
IRF742	400 V	0.8 Ω	8.3 A
IRF742FI	400 V	0.8 Ω	4.5 A
IRF743	350 V	0.8 Ω	8.3 A
IRF743FI	350 V	0.8 Ω	4.5 A

- HIGH VOLTAGE - FOR SWITCHING POWER SUPPLIES
- ULTRA FAST SWITCHING
- EASY DRIVE - FOR REDUCED COST AND SIZE

INDUSTRIAL APPLICATIONS:

- SWITCHING POWER SUPPLIES
- DC SWITCH

N - channel enhancement mode POWER MOS field effect transistors. Easy drive and very fast switching times make these POWER MOS transistors ideal for high speed switching applications. Applications include DC switch, switching power supplies, ultrasonic equipment and electronic ballast for fluorescent lamps.


ABSOLUTE MAXIMUM RATINGS

		TO-220		IRF				
		ISOWATT220		740	741	742	743	
				740FI	741FI	742FI	743FI	
V _{DS} *	Drain-source voltage (V _{GS} = 0)		400	350	400	350		V
V _{DGR} *	Drain-gate voltage (R _{GS} = 20 KΩ)		400	350	400	350		V
V _{GS}	Gate-source voltage				±20			V
I _{DM} (●)	Drain current (pulsed)		40	40	33	33		A
I _{DLM}	Drain inductive current, clamped (L = 100 μH)		40	40	33	33		A
I _D	Drain current (cont.) at T _c = 25°C		10	10	8.3	8.3		A
I _D	Drain current (cont.) at T _c = 100°C		6.3	6.3	5.2	5.2		A
I _D [■]	Drain current (cont.) at T _c = 25°C		740FI	741FI	742FI	743FI		A
I _D [■]	Drain current (cont.) at T _c = 100°C		5.5	5.5	4.5	4.5		A
			3	3	2.5	2.5		A
			TO-220		ISOWATT220			
P _{tot} [■]	Total dissipation at T _c < 25°C		125		40			W
	Derating factor		1		0.32			W/°C
T _{stg}	Storage temperature				-55 to 150			°C
T _j	Max. operating junction temperature				150			°C

* T_j = 25°C to 125°C

(●) Repetitive Rating: Pulse width limited by max junction temperature.

■ See note on ISOWATT220 on this datasheet.

THERMAL DATA

TO-220 | ISOWATT220

$R_{thj - case}$	Thermal resistance junction-case	max	1	3.12	°C/W
R_{thc-s}	Thermal resistance case-sink	typ	0.5		°C/W
$R_{thj-amb}$	Thermal resistance junction-ambient	max	80		°C/W
T_l	Maximum lead temperature for soldering purpose		300		°C

ELECTRICAL CHARACTERISTICS ($T_{case} = 25^\circ\text{C}$ unless otherwise specified)

Parameters	Test Conditions	Min.	Typ.	Max.	Unit
------------	-----------------	------	------	------	------

OFF

$V_{(BR) DSS}$	Drain-source breakdown voltage	$I_D = 250 \mu\text{A}$ for IRF740/742/740FI/742FI for IRF741/743/741FI/743FI	$V_{GS} = 0$	400 350		V V
I_{DSS}	Zero gate voltage drain current ($V_{GS} = 0$)	$V_{DS} = \text{Max Rating}$ $V_{DS} = \text{Max Rating} \times 0.8$	$T_c = 125^\circ\text{C}$		250 1000	μA μA
I_{GSS}	Gate-body leakage current ($V_{DS} = 0$)	$V_{GS} = \pm 20 \text{ V}$			± 500	nA

ON **

$V_{GS (th)}$	Gate threshold voltage	$V_{DS} = V_{GS}$	$I_D = 250 \mu\text{A}$	2	4	V
$I_{D(on)}$	On-state drain current	$V_{DS} > I_{D(on)} \times R_{DS(on) max}$ for IRF740/741/740FI/741FI for IRF742/743/742FI/743FI	$V_{GS} = 10 \text{ V}$	10 8.3		A A
$R_{DS (on)}$	Static drain-source on resistance	$V_{GS} = 10 \text{ V}$ for IRF740/741/740FI/741FI for IRF742/743/742FI/743FI	$I_D = 5.2 \text{ A}$		0.55 0.8	Ω Ω

DYNAMIC

$g_{fs} **$	Forward transconductance	$V_{DS} > I_{D(on)} \times R_{DS(on) max}$ $I_D = 5.2 \text{ A}$		4.0		mho
C_{iss}	Input capacitance	$V_{DS} = 25 \text{ V}$	$f = 1 \text{ MHz}$		1600	pF
C_{oss}	Output capacitance	$V_{GS} = 0$			450	pF
C_{rss}	Reverse transfer capacitance				150	pF

SWITCHING

$t_{d (on)}$	Turn-on time	$V_{DD} = 175 \text{ V}$ $R_l = 4.7 \Omega$	$I_D = 5.0 \text{ A}$		35	ns
t_r	Rise time	(see test circuit)			15	ns
$t_{d (off)}$	Turn-off delay time				90	ns
t_f	Fall time				35	ns
Q_g	Total Gate Charge	$V_{GS} = 10 \text{ V}$ $V_{DS} = \text{Max Rating} \times 0.8$	$I_D = 10 \text{ A}$		63	nC

ELECTRICAL CHARACTERISTICS (Continued)


Parameters	Test Conditions	Min.	Typ.	Max.	Unit
I_{SD} $I_{SDM} (*)$	Source-drain current Source-drain current (pulsed)			10 40	A A
V_{SD}	Forward on voltage	$I_{SD} = 10\text{ A}$	$V_{GS} = 0$	2.0	V
t_{rr}	Reverse recovery time	$T_J = 150^\circ\text{C}$		800	ns
Q_{rr}	Reverse recovered charge	$I_{SD} = 10\text{ A}$	$di/dt = 100\text{ A}/\mu\text{s}$	5.7	μC

** Pulsed: Pulse duration $\leq 300\ \mu\text{s}$, duty cycle $\leq 1.5\%$


(*) Repetitive Rating: Pulse width limited by max junction temperature

■ See note on ISOWATT220 in this datasheet


Safe operating areas (standard package)




Thermal impedance (standard package)




Derating curve (standard package)




Output characteristics




Output characteristics




Transfer characteristics




Transconductance




Static drain-source on resistance




Maximum drain current vs temperature




Gate charge vs gate-source voltage




Capacitance variation




Normalized breakdown voltage vs temperature




Normalized on resistance vs temperature




Source-drain diode forward characteristics




Clamped inductive test circuit




Clamped inductive waveforms



Switching times test circuit



Gate charge test circuit



ABSOLUTE MAXIMUM RATINGS

	TO-220 ISOWATT220	820 820FI	821 821FI	SC-0244 822 822FI	823 823FI
V_{GS}^*	Drain-source voltage ($V_{DS} = 0$)	500	450	500	450
V_{GS}^*	Drain-gate voltage ($P_{GS} = 20$ KJ)	500	450	500	450
V_{GS}	Gate-source voltage	±20	±20	±20	±20
I_{DM}^*	Drain current (pulsed)	8	8	7	7
I_{DM}^*	Drain current (clamped)	8	8	7	7



ISOWATT220 PACKAGE CHARACTERISTICS AND APPLICATION.

ISOWATT220 is fully isolated to 2000V dc. Its thermal impedance, given in the data sheet, is optimised to give efficient thermal conduction together with excellent electrical isolation.

The structure of the case ensures optimum distances between the pins and heatsink. The ISOWATT220 package eliminates the need for external isolation so reducing fixing hardware. Accurate moulding techniques used in manufacture assure consistent heat spreader-to-heatsink capacitance.

ISOWATT220 thermal performance is better than that of the standard part, mounted with a 0.1mm mica washer. The thermally conductive plastic has a higher breakdown rating and is less fragile than mica or plastic sheets. Power derating for ISOWATT220 packages is determined by:

$$P_D = \frac{T_j - T_c}{R_{th}}$$

from this I_{Dmax} for the POWER MOS can be calculated:

$$I_{Dmax} \leq \sqrt{\frac{P_D}{R_{DS(on)} \text{ (at } 150^\circ\text{C)}}$$

THERMAL IMPEDANCE OF ISOWATT220 PACKAGE

Fig. 1 illustrates the elements contributing to the thermal resistance of transistor heatsink assembly, using ISOWATT220 package.

The total thermal resistance $R_{th (tot)}$ is the sum of each of these elements.

The transient thermal impedance, Z_{th} for different pulse durations can be estimated as follows:

1 - for a short duration power pulse less than 1ms;

$$Z_{th} < R_{thJ-C}$$

2 - for an intermediate power pulse of 5ms to 50ms:


$$Z_{th} = R_{thJ-C}$$

3 - for long power pulses of the order of 500ms or greater:

$$Z_{th} = R_{thJ-C} + R_{thC-HS} + R_{thHS-amb}$$


It is often possible to discern these areas on transient thermal impedance curves.

Fig. 1




ISOWATT DATA

Safe operating areas



Thermal impedance



Derating curve

